


# DIGITUS CAT 8.1 field connector, shielded, tool-free mounting connection

DN-93838  
 EAN 4016032499381



### Cat.8.1 Field Termination Plug, shielded, metal screw, and dust cap

The DIGITUS® CAT 8.1 field connector with tool-free installation connection, which impresses with its future-oriented standards and high-end quality for your network. The field connector is suitable for patch cable installation with solid and stranded conductor cables. It conforms to category 8.1 / 25/40GBase-T ISO/IEC 11801, IEC 60603-7-81. The robust metal housing ensures long-lasting, stable connections. The quick assembly without special tools makes this field connector the ideal choice for installation, repair and maintenance.

### 25/40GBase-T transmission speed in permanent link up to 24 m and channel link up to 30 m

- Transmission characteristics:
- Category 8.1 - 25/40 GBase-T, 2000 MHz
- ISO/IEC 11801 3rd Edition, EN 50173-1
- Suitable for PoE/PoE+/4PPoE (IEEE 802.3af, 3at, 3bt)
- General specifications:
- Tool-free cable installation via LSA cutting terminals, color-coded according to EIA/TIA 568 A&B

- Strain relief and cable fixation with screw cap
- RJ45 plug, 8P8C
- 360° shield contacting
- Technical specifications:
- Housing material: die-cast zinc
- Contact material: Phosphor bronze
- Coating of the contacts: Nickel, gold-plated 0.5 μ
- Physical specifications:
- Insertion force: Max. 30N (according to IEC 60603-7-81)
- Operating temperature: -20°C up to +70°C (ISO/IEC 11801, ANSI/TIA 568 C.2)
- Mating cycles: > 1500 (ISO/IEC 11801, IEC 60603-7-81)
- Copper conductor diameter: AWG (26/7 - 22/1), stranded and solid wire
- Dielectric strength: 1000 VDC (contact/contact), 1500 VDC (contact/ground)

### Attributes

- Category: CAT 8.1

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm <sup>3</sup>
Packaging Unit Carton	500	9.50	0.00	0.00	0.00	0.00
Packaging Unit Inside	1	0.00	0.00	0.00	0.00	0.00
Packaging Unit Single	1	0.00	0.00	0.00	0.00	0.00
Net single without Packaging	0	0.00	0.00	0.00	0.00	0.00

**More images:****Safety notes**

- Protect product from moisture
- Avoid antistatic charging when installing the product
- Observe the specifications of the raw cable manufacturer during installation

**EU responsible person**

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH  
Auf dem Schüffel 3  
Lüdenscheid, Germany  
<https://www.assmann.com>  
[info@assmann.com](mailto:info@assmann.com)