

# ednet DVI Connection Cable

## ED-84521 EAN 4054007845214





#### DVI connection cable, DVI(24+1), 2x ferrit M/M, 3.0m, DVI-D Dual Link, cotton, gold, bl

This digital, Full HD suitable DVI cable (Dual Link), is used to connect audio/video equipment with DVI(24+1) interface, such as PC, notebook, monitor, TV or a projector, for example.

### Full HD, Dual-Link

• Support up to 2560 x 1600 pixel with 30Hz

## **Attributes**

- · Assortment: DVI Cables
- AWG: 30

- Color cable: black
- Color connector: black
- Connector 1: DVI-D, (24+1), plug Connector 2: DVI-D, (24+1), plug
- Connector surface: gold-plated
- Ferrite filter: 2 x ferrite beads
- HDTV Resolution max.: 2560 x 1600 Pixel, 60Hz
- HDTV Standard: Full HD
- Hoods: molded
- Wire material: CU
- Length: 3 m
- Shielding: triple shielding

| Logistics                    |                 |                |               |               |                |       |
|------------------------------|-----------------|----------------|---------------|---------------|----------------|-------|
|                              | Number<br>(pcs) | Weight<br>(kg) | Depth<br>(cm) | Width<br>(cm) | Height<br>(cm) | cm³   |
| Packaging Unit Carton        | 20              | 9.90           | 67.00         | 30.00         | 35.00          | 70.35 |
| Packaging Unit Inside        | 1               | 0.50           | 32.00         | 28.00         | 16.00          | 14.34 |
| Packaging Unit Single        | 1               | 0.50           | 6.00          | 15.00         | 23.50          | 2.12  |
| Net single without Packaging | 0               | 0.50           | 6.00          | 15.00         | 23.50          | 2.12  |

## More images:





#### Safety notes

• When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.



- · Cables must not be kinked sharply or bent at tight angles, as this can damage the inner wires and lead to failures.
- Make sure that the cables are not under tensile load, as this can damage the insulation and the wires inside the cable.
- Ensure that cables are not laid in areas where they can be easily damaged mechanically.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product specifications for the maximum operating temperature of the cable
- Check cables regularly for visible damage such as cracks, kinks or signs of wear. Defective cables should be replaced immediately to avoid failures, short circuits or even electric shocks.

## EU responsible person

 $\ensuremath{\mathsf{EU}}$  based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH Auf dem Schüffel 3 Lüdenscheid, Germany https://www.assmann.com info@assmann.com