

PURELINK 4K HDBaseT Transmitter with PoH

PT-HDBT-702-TX
EAN 4251364706763



PT-HDBT-702-TX is a fully HDBaseT compliant transmitter. It is able to transmit Full HD up to 70m and 4K/UHD up to 40m with embedded multi-channel audio, and control signals. It is even CEC capable allowing the pass through of CEC to simplify system control with a single remote. Its two way PoH allows for remote powering of a sink or receiver, or can be powered from any other PoH capable device. Connections Input connector(s) 1 x HDBaseT (RJ45) Output connector(s) 1 x HDMI Power connector(s) DC 24V, 1.25A Control connector(s) 1 x IR Input (3,5mm Klinke); Electric signal Maximum data rate 1080p < 70M; 4K < 40M Standards HDMI 1.4a & HDCP2.2 HDCP T EDID T Mechanical Power supply DC 24V, 1,25A Power consumption 14W max. Operating temperature 0°C ~ 50°C Humidity 10% ~ 90% Dimensions 115mm x 16.2mm x 109 Signal transmission Supported standards HDMI1.4a und HDCP 2.2

- PT-HDBT-702-TX is a fully HDBaseT compliant transmitter.
- Compatible with 4K HDMI sources and displays, displaying signals at resolutions up to 4K @60 4:2:0 (10.2Gbps).
- With CEC pass through, smart EDID management, IR and RS232 pass through, the PT-HDBT-702-TX is perfectly equipped to handle all your data without difficulties. Simply plug and play.
- With HDBaseT transmission up to 40m range at 4K (70m at 1080p), and two way PoH, the PT-HDBT-702-TX is a professional HDBaseT transmitter for use with all HDBaseT rated equipment.
- All of this technology is packed into an ultra slim light weight enclosure, for installation almost anywhere.
- AOC - Active Optical Cable: no
- KVM: no
- PoE (Power over Ethernet): no

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm ³
Packaging Unit Carton	24	0.00	0.00	0.00	0.00	0.00
Packaging Unit Inside	0	0.00	0.00	0.00	0.00	0.00
Packaging Unit Single	1	0.27	0.00	0.00	0.00	0.00
Net single without Packaging	0	0.27	0.00	0.00	0.00	0.00