

# PURELINK IS2510-005 Easy connection between USB-C devices incl. USB Power Delivery

IS2510-005  
EAN 4251364709672



The Premium USB-C (male) to USB-C (male) cable connects two USB-C devices compliant to the USB 3.1 (Gen 2) standard with a maximum data transfer rate of 10Gbps. The cables can also be used as charging cables for USB-C devices and support USB Power Delivery with max. 5A / 20V / 100W. The cable is equipped with nickel-plated connectors and features high-purity and triple shielded copper conductors. Available in lengths between 0.50m - 1.50m. Connections Shielding Yes Connector 1 USB-C male Connector 2 USB-C male Electric signal Maximum data rate Gen 2 - 10Gbps Cable Type Round Cable Length 0.50m Inner conductor material Tinned Copper AWG AWG30/32/34/26 Number of shieldings 3 Shielding 1 Aluminium foil Marla (100% density) Shielding 3 Braid (90% density) Outer material Very elastic PVC Outer diameter 5.2±0.2mm Signal transmission Transmission

modes Data and power Others: Safety RoHS, REACH Colour white

- USB 3.1 (Gen 2) - 10Gbps data transmission
- Gold plated precision contacts
- USB-C male to USB-C male
- High purity copper conductors and triple shielding
- USB Power Delivery with 5A / 20V / 100W; without PD max. 3A / 5V / 15W
- Color cable: black
- Connector 1: USB C, plug
- Connector 2: USB C, plug
- Length: 0.5 m
- USB-C Products: yes

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	120	0.00	0.00	0.00	0.00	0.00
Packaging Unit Inside	0	0.00	0.00	0.00	0.00	0.00
Packaging Unit Single	10	0.02	0.00	0.00	0.00	0.00
Net single without Packaging	0	0.02	0.00	0.00	0.00	0.00

## More images:

