

PURELINK FiberX Series - HDMI 4K Fiber Portsaver Extender mit SLS

FX-P350
EAN 4251364712146



FiberX® - FX Series. HDMI 4K Pigtail Fiber Optic Extender. 1xSC Multimode (Single Fiber). 4K up to 1000m. Plug & Play (CEC, EDID, HDCP). Included in delivery: Transmitter (TX), Receiver (RX), 2x USB Cable, Manual EN/DT. Connections Output connector(s) Status LED: power, video and HDCP status Power connector(s) Tx: 5V1A USB or HDMI | Rx: 5 Control connector(s) Firmware via USB Connector 1 Tx: HDMI Plug | Rx: SC Simplex Socket Connector 2 Tx: SC Simplex Buchse | Rx: HDMI Socket Dimensions Con.1 HDMI: 37 x 18 x 14 mm Dimensions Con.2 SC Modul: 88 x 30 x 12 mm Contacts 24kt. gold-plated Electric signal Maximum data rate 18 Gbps Maximum pixel clock / bandwidth 18 Gbps Standards Laser Wavelength HSL: 780, 800, 825, 850 nm; LSL: HDCP Yes CEC Yes EDID Yes Cable Type Glass fiber pigtail ex Lenght HDMI: 270mm | USB: 1000mm Inner conductor

material Copper / fiberglass Outer material PVC / aluminum Outer diameter HDMI: ca. 6mm Mechanical Power supply USB 5V Power consumption Tx: 1,5W/2W / Rx: 0, Operating temperature 0°C bis +50°C Storage temperature -40°C bis +85°C Humidity 10% bis 90% Enclosure aluminum, passiva ge Dimensions 110,5 x 35,5 x 11 x Signal transmission Supported standards HDMI 1.4 + 2.0, SC Fiber, HDCP (1.4/2.2), etc. Transmission modes Digital audio and video signals with 0 frames delay Supported Colors Up to HDR 10, HDR 12 and Dolby Vision, RGB, YCbCr 4:4:4, YCbCr 4:2:2, YCbCr 4:2:0 Supported audio standards Up to Dolby Atmos bzw. DTS HD Master Audio Maximum resolution 4K / UltraHD / 20160p (4096x2160) @60Hz, 4:4:4 Additional Safety CE, FCC, REACH, ROHS Colour Black

- AOC - Active Optical Cable: no

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	1	0.00	0.00	0.00	0.00	0.00
Packaging Unit Inside	0	0.00	0.00	0.00	0.00	0.00
Packaging Unit Single	1	0.16	0.00	0.00	0.00	0.00
Net single without Packaging	0	0.13	0.00	0.00	0.00	0.00