

PURELINK Purelink PureTools PT-C-HDSDI

PT-C-HDSDI
EAN 4260134117074



The PT-C-HDSDI provides a professional way to convert HDMI to 3G/HD/SD SDI in real time. The conversion between SDI and HDMI is pure digital and guarantees no loss transformation for both audio and video. Video: HDMI with HDCP, 3D and DeepColor support Resolution up to fullHD 1080p (1920x1080) and WUXGA (1920x1200) 3G support up to fullHD 1080p/50/59.94/60Hz (4:2:2) HD support up to fullHD 1080p23.98/24/25/29.97/30Hz SD support up to NTSC/59.94Hz und PAL/50Hz Audio: Supports 8 CH audio incl.7.1 channel DTS-HD Master and Dolby TrueHD

- Conversion of HDMI and 3G/HD-SDI signals in real time
- Supports HDMI incl. Deep Color and HDTV resolution up to 1080p (1920x1080)

- Supports 8 CH audio incl.7.1 channel DTS-HD Master and Dolby TrueHD
- Auto 3G/HD-SDI detection
- Supports HDCP
- External DIP-Switch configuration possible
- Additional BNC output for Daisy-Chain applications
- Screw-power connector
- Especially suitable for professional AV applications and installations

Attributes

- AOC - Active Optical Cable: no
- Audio: no

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	20	4.00	0.00	0.00	0.00	0.00
Packaging Unit Inside	1	0.20	0.00	0.00	0.00	0.00
Packaging Unit Single	1	0.20	0.00	0.00	0.00	0.00
Net single without Packaging	0	0.00	0.00	0.00	0.00	22.80

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

Bachmann GmbH
Ernstthalenstr. 33
Stuttgart, Germany
<https://www.bachmann.com/de/>
info@bachmann.com