

# Planet Fast Ethernet Medienkonverter, RJ45 / ST

PL-FT-801  
EAN 4711213680519



## Planet Bridge Media Converter, RJ45-ST, 100Mbps,

Fiber Optic Bridge Converter, 100 Mbps, 10/100Base-TX (RJ45) to 100Base-FX (ST, MM), desktop case with external power supply, supports LFP (Link Fault Pass Through function) means LLCF (Link Loss Carry Forward) and LLR (Link Loss Return) may be installed in MC-Chassis

- Transforms wire based network media to fiber optic
- High quality and excellent reliability
- 10/100Base-TX to 100Base-FX (ST,MM)
- Connectors: 1x RJ45, 1x ST Duplex
- Distance: up to 2km
- Multimode dual fiber
- Automatic cable detection - auto MDI / MDI-X function
- Auto-negotiation of full- and half-duplex

- Diagnostic and monitoring LEDs for the status of power, link and act of the ports
- Link Fault Pass Through (LFP) function for easier network maintenance
- Suitable for 50/125µm and 62.5/125µm Fiber Cables
- Transmission power: minimum -22 dBm, maximum -12 dBm
- Sensitivity Receiving Power: Minimum -32 dBm
- Supported Standards: IEEE 802.3 Ethernet, IEEE 802.3u Fast Ethernet
- Operating temperature: 0 to 50 °C
- Input Supply Voltage: 5V DC
- Standalone Converter with external power supply
- Dimensions (L x W x H): 97mm x 69mm x 26mm
- Industrial usage: no
- PoE injector: no

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm <sup>3</sup>
Packaging Unit Carton	20	14.00	59.00	36.00	30.00	63.70
Packaging Unit Inside	1	0.70	28.00	14.00	2.50	980.00
Packaging Unit Single	0	0.50	28.00	14.00	2.50	980.00
Net single without Packaging	0	0.50	11.00	7.00	2.50	192.50

## More images:

