

Planet Industrial Fast Ethernet Media Converter RJ45 / SC, 15km

PL-IFT-802TS15
EAN 4711213687563



Planet IP30 Slim Industrial Converter, 10/100, RJ45/SC SM-15KM

Fiber Optic Bridge Converter, 10/100Base-TX (RJ45) to 100Base -FX (SC, SM-15KM), IP-30 Aluminium Industry , Auto MDI / MDI -X , half / full duplex, Supports 6KV DC Ethernet ESD protection, Supports 6KV DC EFT protection for power line, operating temperature -40 - 75 degrees C, for DIN- rail and wall mounting , Dimension (W x D x H) 135 x 85 x 32 mm, internal power supply for 12 - 48V DC

The best Solution for rough Environmental Conditions!

- 1-Port 10/100Base-T RJ-45
- 1 Port 100Base-FX SC interface, provides long distance for 15km
- Redundant Power Design: 12-48V DC redundant power with polarity reverse protect function
- IP-30 protection with metal case
- DIN rail and wall mount design
- Relay alarm for port breakdown and power failure
- Free fall, Shock and Vibration Stability

- Complies with the IEEE 802.3 and IEEE 802.3u Standards
- Supports Auto-Negotiation and 10/100Mbps half / full duplex mode
- High performance Store and Forward architecture
- Prevents packet loss with back pressure (Half-Duplex) and IEEE 802.3x PAUSE frame flow control (Full-Duplex)
- Supports to handle up to 1522bytes packet size
- Connector 1: RJ45
- Connector 2: SC
- Mode: Singlemode
- Distance (km): 15
- DDM Support: no
- Industrial usage: yes
- Broadcasting Mode: Unidirectional
- PoE injector: no
- Ethernet speed: Fast Ethernet

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm ³
Packaging Unit Carton	20	21.00	39.50	44.50	53.00	93,178.30
Packaging Unit Inside	1	1.05	5.00	21.00	15.00	1.60
Packaging Unit Single	1	0.43	5.00	21.00	15.00	1.60
Net single without Packaging	0	0.43	0.00	0.00	0.00	0.00

More images:

