

NOCTUA Noctua Case Fan 120 mm

NOC-NF-S12A-FLX
EAN 4716123314905



- Size: 120x120x25 mm
- Connector 3-pin
- Bearing SSO2
- Blade Geometry S-Series with Anti-Stall Knobs
- Frame Technology AAO (Advanced Acoustic Optimisation)
- Rotational Speed (+/- 10%) 1200 RPM
- Rotational Speed with L.N.A. (+/- 10%): 900 RPM
- Rotational Speed with U.L.N.A. (+/- 10%): 700 RPM
- Airflow: 107,5 m³/h
- Airflow with L.N.A.: 83,2 m³/h
- Airflow with U.L.N.A.: 65,8 m³/h
- Acoustical Noise: 17,8 dB(A)
- Acoustical Noise with L.N.A.: 10,7 dB(A)
- Acoustical Noise with U.L.N.A.: 7,4 dB(A)

- Static Pressure: 1,19 mm H2O
- Static Pressure with L.N.A.: 0,73 mm H2O
- Static Pressure with U.L.N.A.: 0,51 mm H2O
- Max. Input Power: 1,44 W
- Max. Input Current: 0,12 A
- Voltage: 12 V

Package contents

- Low-Noise Adaptor (L.N.A.)
- Ultra-Low-Noise Adaptor (U.L.N.A.)
- 3:4-Pin Adaptor
- 30cm Extension Cable
- 4 Vibration-Compensators
- 4 Fan Screws

| Logistics | | | | | | |
|------------------------------|--------------|-------------|------------|------------|-------------|------|
| | Number (pcs) | Weight (kg) | Depth (cm) | Width (cm) | Height (cm) | cm³ |
| Packaging Unit Carton | 36 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |
| Packaging Unit Inside | 0 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |
| Packaging Unit Single | 1 | 0.29 | 0.00 | 0.00 | 0.00 | 0.00 |
| Net single without Packaging | 0 | 0.29 | 0.00 | 0.00 | 0.00 | 0.00 |

More images:



