

NOCTUA Noctua Case Fan 120 mm

NOC-NH-U14S
EAN 4716123314950



Fan specifications Model Noctua NF-A15 PWM Bearing SSO2 Max. Rotational Speed (+/- 10%) 1500 RPM Max. Rotational Speed with L.N.A. (+/- 10%) 1200 RPM Min. Rotational Speed (PWM) 300 RPM Max. Airflow 140,2 m³/h Max. Airflow with L.N.A. 115,5 m³/h Max. Acoustical Noise 24,6 dB(A) Max. Acoustical Noise with L.N.A. 19,2 dB(A) Input Power 1,56 W Voltage Range 12 V MTBF > 150.000 h

- Socket compatibility: Intel LGA2011 (Square ILM), LGA1156, LGA1155, LGA1150 & AMD AM2, AM2+, AM3, AM3+, FM1, FM2 (backplate required)
- Height (without fan): 165 mm
- Width (without fan): 150 mm
- Depth (without fan): 52 mm
- Height (with fan): 165 mm

- Width (with fan): 150 mm
- Depth (with fan): 78 mm
- Material: Copper (base and heat-pipes), aluminium (cooling fins), soldered joints & nickel plating
- Fan compatibility: 140x150x25 (with 120mm mounting holes), 140x140x25 (with 120mm mounting holes), 120x120x25

Package contents

- NF-A15 PWM premium fan
- Low-Noise Adaptor (L.N.A.)
- NT-H1 high-grade thermal compound
- SecuFirm2™ Mounting Kit
- Anti-vibration pads and fan-clips for second NF-A15 (optional)
- Noctua Metal Case-Badge

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	0	0.00	0.00	0.00	0.00	0.00
Packaging Unit Inside	0	0.00	0.00	0.00	0.00	0.00
Packaging Unit Single	0	0.00	0.00	0.00	0.00	0.00
Net single without Packaging	0	0.00	0.00	0.00	0.00	0.00

More images:

