

# NOCTUA NOCTUA NF-A8 FLX

**NOC-NF-A8-FLX**  
**EAN 4716123315483**



The NF-A8 is a highly optimised, premium quality quiet 80mm fan. Featuring Noctua's AAO (Advanced Acoustic Optimisation) frame as well as sophisticated aerodynamic design measures such as Flow Acceleration Channels, the NF-A8 further improves the renowned quiet cooling performance of the award-winning NF-R8. The FLX version provides 2000/1650/1200rpm speed settings via the supplied Low-Noise Adaptors in order to provide full flexibility in fine-tuning the fan for maximum ventilation performance or near-silent operation. Its superb running smoothness, reference-class SSO2 bearing and Noctua's trusted premium quality make it an elite choice for the highest demands.

- Size: 80x80x25 mm
- Connector: 3-pin
- Bearing: SSO2
- Blade Geometry: A-Series with Flow Acceleration Channels
- Frame Technology: AAO (Advanced Acoustic Optimisation)

- Rotational Speed (+/- 10%): 2000 RPM
- Rotational Speed with L.N.A. (+/- 10%): 1650 RPM
- Rotational Speed with U.L.N.A. (+/- 10%): 1200 RPM
- Airflow: 50,4 m³/h
- Airflow with L.N.A.: 41,4 m³/h
- Airflow with U.L.N.A.: 28,9 m³/h
- Acoustical Noise: 16,1 dB(A)
- Acoustical Noise with L.N.A.: 12,9 dB(A)
- Acoustical Noise with U.L.N.A.: 7,9 dB(A)
- Static Pressure: 1,92 mm H2O
- Static Pressure with L.N.A.: 1,40 mm H2O
- Static Pressure with U.L.N.A.: 0,74 mm H2O
- Max. Input Power: 0,84 W
- Max. Input Current: 0,07 A
- Voltage: 12 V
- MTBF > 150.000 h

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	40	0.00	0.00	0.00	0.00	0.00
Packaging Unit Inside	0	0.00	0.00	0.00	0.00	0.00
Packaging Unit Single	1	0.25	0.00	0.00	0.00	0.00
Net single without Packaging	0	0.25	0.00	0.00	0.00	0.00

## More images:



