

NOCTUA Noctua NF-A9-PWM

NOC-NF-A9-PWM
EAN 4716123315513



The NF-A9 is a highly optimised, premium quality quiet 92mm fan. Featuring Noctua's AAO (Advanced Acoustic Optimisation) frame as well as sophisticated aerodynamic design measures such as Flow Acceleration Channels, the NF-A9 further improves the renowned quiet cooling performance of the award-winning NF-B9. The PWM version sports Noctua's custom designed NE-FD1 IC for fully automatic speed control via 4-pin fan headers and comes with a Low-Noise-Adaptor to reduce the maximum speed during PWM control from 2000 to 1550rpm. Its superb running smoothness, reference-class SSO2 bearing and Noctua's trusted premium quality make it an elite choice for the highest demands.

- Size: 92x92x25 mm
- Connector: 4-pin PWM
- Bearing: SSO2
- Blade Geometry: A-Series with Flow Acceleration Channels

- Frame Technology: AAO (Advanced Acoustic Optimisation)
- Rotational Speed (+/- 10%): 2000 RPM
- Rotational Speed with L.N.A. (+/- 10%): 1550 RPM
- Min. Rotational Speed (PWM): 400 RPM
- Airflow: 78,9 m³/h
- Airflow with L.N.A.: 62,6 m³/h
- Acoustical Noise: 22,8 dB(A)
- Acoustical Noise with L.N.A.: 16,3 dB(A)
- Static Pressure: 2,28 mm H₂O
- Static Pressure with L.N.A.: 1,53 mm H₂O
- Max. Input Power: 1,2 W
- Max. Input Current: 0,1 A
- Voltage: 12 V
- MTBF: > 150.000 h

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm ³
Packaging Unit Carton	40	0.00	0.00	0.00	0.00	0.00
Packaging Unit Inside	0	0.00	0.00	0.00	0.00	0.00
Packaging Unit Single	1	0.24	0.00	0.00	0.00	0.00
Net single without Packaging	0	0.24	0.00	0.00	0.00	0.00

More images:



