

NOCTUA NOCTUA NF-A6x25 PWM

NOC-NF-A6X25-PWM
EAN 4716123315636



Featuring advanced aerodynamic design measures such as Flow Acceleration Channels and Noctua's AAO frame, the NF-A6x25 is a highly optimised, premium quality quiet fan in 60x25mm size. The PWM version sports Noctua's custom designed NE-FD1 IC for fully automatic speed control via 4-pin fan headers and comes with a Low-Noise-Adaptor to reduce the maximum speed during PWM control from 3000 to 2100rpm. Its superb running smoothness, SSO2 bearing and Noctua's trusted premium quality make it an elite choice for the highest demands.

- Size: 60x60x25 mm
- Mounting hole spacing: 50x50 mm
- Connector: 4-pin PWM
- Bearing: SSO2
- Blade Geometry: A-Series with Flow Acceleration Channels

- Frame Technology: AAO (Advanced Acoustic Optimisation)
- Rotational Speed (+/- 10%): 3000 RPM
- Rotational Speed with L.N.A. (+/- 10%): 2100 RPM
- Min. Rotational Speed (PWM, +/-20%): 550 RPM
- Airflow: 29,2 m³/h
- Airflow with L.N.A.: 22,6 m³/h
- Acoustical Noise: 19,3 dB(A)
- Acoustical Noise with L.N.A.: 13,7 dB(A)
- Static Pressure: 2,18 mm H2O
- Static Pressure with L.N.A.: 1,29 mm H2O
- Max. Input Power: 0,96 W
- Max. Input Current: 0,08 A
- Voltage: 12 V
- MTBF > 150.000 h

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	36	0.00	0.00	0.00	0.00	0.00
Packaging Unit Inside	0	0.00	0.00	0.00	0.00	0.00
Packaging Unit Single	1	0.27	0.00	0.00	0.00	0.00
Net single without Packaging	0	0.27	0.00	0.00	0.00	0.00

More images:



