

Mean Well Power supply DIN rail 24 V, 5 A

MW-NDR-120-24
EAN 7612946523326



Mean Well 120W 24V DC Industrial DIN Rail Power Supply (-20 to +70°C)

Single Output 120 Watt power supply for Planet industrial switches and converters. Universal input 90-264V AC, Output 24-28V DC (0-5A)
Protection: Short circuit / overload / over voltage, for mounting on DIN rail TS-35 / 7.5 / 15, Dimensions (WxHxD) 40x125.2x113.5mm

- Output voltage: 24 V
- Output current: max. 5 A
- Power: 120 W

- Ripple & noise: 150 mVpp
- Efficiency: 89% Universal AC input / full range
- Protections: short circuit, overload, over voltage, over temperature
- Cooling by free air convection
- Can be installed on DIN rail TS-35/7.5 or 15
- UL 508 approved
- EN61000-6-2 (EN50082-2) industrial immunity level
- 100% full load burn-in test

| Logistics | | | | | | |
|------------------------------|--------------|-------------|------------|------------|-------------|-----------------|
| | Number (pcs) | Weight (kg) | Depth (cm) | Width (cm) | Height (cm) | cm ³ |
| Packaging Unit Carton | 0 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |
| Packaging Unit Inside | 0 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |
| Packaging Unit Single | 0 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |
| Net single without Packaging | 0 | 0.00 | 0.00 | 0.00 | 0.00 | 1.75 |

More images:



EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

MEAN WELL EUROPE N.V.
Langs de Werf 8
Amstelveen, Netherlands
<https://www.meanwell.eu>
info@meanwell.eu