

NOCTUA

NOC-NF-A4X10-PWM
EAN 9010018100440



NOCTUA NF-A4x10-PWM Featuring advanced aerodynamic design measures such as Flow Acceleration Channels and Noctua's AAO frame, the NF-A4x10 is an award-winning, premium-quality quiet fan in size 40x10mm. The PWM version sports Noctua's custom-designed NE-FD1 IC for fully automatic speed control via 4-pin fan headers and comes with a Low-Noise Adaptor as well as an Omnijoin Adaptor Set for easy connection to proprietary fan headers. Its superb running smoothness, reference-class SSO2 bearing and Noctua's trusted premium quality make it an elite choice for the highest demands.

- Size: 40x40x10 mm
- Mounting hole spacing: 32x32 mm
- Connector: 4-pin PWM
- Bearing: SSO2
- Cable length: 20cm + 30cm NA-EC1 extension cable
- Blade geometry: A-Series with Flow Acceleration Channels
- Frame technology: AAO (Advanced Acoustic Optimisation)
- Rotational speed (+/- 10%): 5000 RPM
- Rotational speed with L.N.A. (+/- 10%): 3700 RPM

- Min. rotational speed (PWM, +/-20%): 1000 RPM
- Airflow: 8,9 m³/h
- Airflow with L.N.A.: 6,6 m³/h
- Acoustical noise: 19,6 dB(A)
- Acoustical noise with L.N.A.: 12,9 dB(A)
- Static pressure: 1,95 mm H₂O
- Static pressure with L.N.A.: 1,21 mm H₂O
- Max. input power: 0,48 W
- Max. input current: 0,04 A
- Operating voltage: 12 V
- MTTF: > 150.000 h

Package contents

- 30cm Extension Cable
- NA-AV3 anti-vibration mounts
- Omnijoin Adaptor Set
- 4-pin y-cable
- Low-Noise Adaptor (L.N.A.)
- 4 Fan Screws

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm ³
Packaging Unit Carton	36	0.00	0.00	0.00	0.00	0.00
Packaging Unit Inside	0	0.00	0.00	0.00	0.00	0.00
Packaging Unit Single	1	0.19	0.00	0.00	0.00	0.00
Net single without Packaging	0	0.16	0.00	0.00	0.00	0.00

More images:

