

# MIKROTIK Mikrotik RBcAPGi-5acD2nD - cAP ac

**M-RBCAPGI-5ACD2ND**  
**EAN 9010386006849**



The cAP ac is a very capable and powerful wireless access point that looks beautiful on both walls and ceilings. The concurrent dual band wireless radio supports dual chain 2 GHz and 5 GHz in 802.11ac and legacy standards, and will provide coverage in 360 degrees around it. Even though the radio supports repeater mode, the two Ethernet ports give you the ability to extend your network with cables, even if PoE power is required, since the cAP ac supports 802.3af/at PoE input on the first port, and passive PoE output on the second port.

- CPU: 4 cores, IPQ-4018
- CPU nominal frequency: 716 MHz
- Memory: 128 MB
- Storage type: Flash
- Storage size: 16 MB
- 10/100/1000 Ethernet ports: 2
- Wireless:
  - 2.4 GHz
  - 5 GHz
- Operating frequency:
  - 2412 - 2484 MHz
  - 5150 - 5875 MHz
- Protocols:
  - 802.11b/g/n

- 802.11ac
- Number of chains: 2
- Antenna gain:
  - 2 dBi (2.4 GHz)
  - 2.5 dBi (5 GHz)
- Wireless regulations: Specific frequency range may be limited by country regulations
- Power options: PoE-in 802.3af/at, PoE-out (Passive, Ethernet port 2), 17-57 V
- Consumption: 13 W
- Dimensions:
  - Round case: ? 136 mm, height: 30 mm
  - Square case: 145 x 145 x 30 mm
- Operating temperature: -40°C to +50°C tested
- LEDs: 7x LEDs (1x user LED)
- License level: 4
- Operating system: RouterOS

#### Package contents

- 24 V, 1.2 A power adapter
- Ceiling mount
- Gigabit PoE injector
- K-46 screw kit

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm <sup>3</sup>
Packaging Unit Carton	1	0.00	0.00	0.00	0.00	0.00
Packaging Unit Inside	0	0.00	0.00	0.00	0.00	0.00
Packaging Unit Single	1	1.00	0.00	0.00	0.00	0.00
Net single without Packaging	0	0.80	0.00	0.00	0.00	0.00