

DIGITUS aluminum outlet strip with overload protection, 7 safety outlets, 2 m supply safety plug

DN-95403
EAN 4016032266419



1U Aluminum PDU, rackmountable, 7x safety outlet 16A, 4000W, 250VAC 50/60Hz, overload protection

The DIGITUS® power distribution units are the perfect solution for you 482.6 mm (19") network- or server cabinet. Optimized for rack installation with 220-240V 50-60 Hz the DIGITUS® PDU offer you the best performance with qualified efficiency. The 482.6 mm (19") fixing material provides an optimized enclosing on the profile rails of your cabinets. Every PDU can be mounted horizontally as well as vertically and has the possibility, according to the cabinet, to be mounted faced up or down.


Safe and professional power in the 482.6 mm (19") range

- 7x safety outlets 250VAC 50/60Hz / 16A / 4000W
- Aluminium profile
- 2x angle profiles for cabinet mounting

- 2 m Cable H05VV-F 3G1,5 mm² with safety plug
- Plastic components made by ABS UL-94V-0
- Grounding on aluminium profile
- 35° turned safety outlets
- Overload protection : Interrupt Capacity - 1000 A
- Additional Features: Power switch
- Current: 16 A
- Input Plug: CEE7/7
- Installation: Desktop, Rack 0U, Rack 1U
- Outlets: CEE 7/3
- Phase: 1ph
- Power: 3,6 kVA
- Volts: 230 V
- Inch form factor (IEC 60297): 482.6 mm (19")

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	20	21.00	51.00	46.00	27.00	0.00
Packaging Unit Inside	1	1.05	6.70	50.00	9.10	0.00
Packaging Unit Single	1	1.05	6.70	50.00	9.10	0.00
Net single without Packaging	0	0.76	4.40	48.20	4.40	933,152.00

More images:



Aluminum Outlet Strip with Overload Protection, 7 Safety Outlets, 2m Supply Safety Plug

