

# DIGITUS CAT 3 ISDN Patch Panel, unshielded, grey

DN-91325-1  
EAN 4016032269007



**CAT 3 ISDN Patch Panel, unshielded, 25-port RJ45, 8P4C, LSA, 1U, rack mount, grey, 482x44x109**

The ISDN Patch Panels from DIGITUS® are available as 25- or 50-port version. With 1.5 mm galvanized cold-rolled steel they are perfectly suitable for 19" rack mounting.

**Future-oriented standards and high-end quality for your network.**

- Suitable for 483 mm (19") rack mount
- Suitable for cables with AWG 22-26 diameter
- Material housing: SECC, 1.5 mm electrogalvanized, cold-rolled steel acc. EN1.4301, UNS S30400, AISI 304 and LMSAD110
- RJ45 female, 8P4C
- Unshielded RJ45 jacks
- Material contacts: Phosphor bronze
- Contacts coating: Nickel, gold plated 0,3µ

- Cable installation via LSA strips, color coded according to EIA/TIA 568 A & B
- Material IDC Terminal: Phosphor bronze with 50 µ tin plated over 60 µ nickel plated
- Material PCB: FR4, UL 94V-0, multilayer 1.45 mm thickness
- Insertion force: ≤ 30 N
- Mating cycles: ≥ 750 (ISO/IEC 11801, IEC 60603-7-5)
- Operating temperature: -20°C ... +70°C
- Current carrying capacity: 1A at 50 °C
- Isolation resistance > 500MΩ
- Color: Grey (RAL 7035)
- Color: light grey, RAL 7035
- Ports: 25
- Units: 1
- Category: CAT 3

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	10	14.46	53.50	32.00	28.00	0.00
Packaging Unit Inside	1	1,446.00	5.20	51.30	14.80	0.00
Packaging Unit Single	1	1,446.00	51.50	5.50	10.50	0.00
Net single without Packaging	0	0.96	10.00	48.20	4.30	0.00

**More images:**

