

DIGITUS CAT 6 Modular plugs for round cable, Pass through connector

AK-219603
EAN 4016032316817



CAT 6 Modular Plug, 8P8C, shielded for Round Cable, pass through connector

Easy assembly by modular crimping tool DN-94004

- Crimping tool – DN-94025 (Multi Modular Crimping Tool Pass through connectors)
- Layout performance: CAT 6, 1GBase-T
- Area of application: Patch cable assembly
- Norms: ISO/IEC 11801 3rd Ed., EN 50173-1, EIA/TIA 568-C
- General properties:
- UL certified

- Technical properties:
- Mating cycles female: > 750 acc. to ISO/IEC 11801, IEC 60603-7-5
- Material connector body: Polycarbonat, clear
- Connector contact: Phosphor bronze, brass 0.6 μ gold-plated
- Flammability: UL 94V-2
- Physical properties:
- Insertion force: ≤ 30 N
- Diameter Cu-Conductor: AWG (27/7 ... 24/7)
- Operating temperature: -40 °C to +80 °C
- Current carrying capacity: 1A -1.5A at 50 °C

| Logistics | | | | | | |
|------------------------------|--------------|-------------|------------|------------|-------------|-----------------|
| | Number (pcs) | Weight (kg) | Depth (cm) | Width (cm) | Height (cm) | cm ³ |
| Packaging Unit Carton | 0 | 11.80 | 41.00 | 38.00 | 21.00 | 0.00 |
| Packaging Unit Inside | 100 | 236.00 | 17.00 | 13.00 | 3.00 | 663.00 |
| Packaging Unit Single | 1 | 0.00 | 2.00 | 1.00 | 0.50 | 1.00 |
| Net single without Packaging | 0 | 0.00 | 3.00 | 3.00 | 1.50 | 13.50 |