

DIGITUS Gigabit Ethernet PoE+ Repeater, 802.3at, 22 W

DN-95123
EAN 4016032391531



Gigabit Ethernet PoE+ Extender, 802.3at 1-port, Power Pins:3/6(+), 1/2(-), 22W

The DIGITUS Gigabit PoE+ Extender, uses the advanced network cable and power technology to extend your Ethernet signal up to 100m per unit (total 500m). The Extender is self powered by PoE, so there is no additional power supply needed. This enables you to use the device even where no power lines or outlets are available. You can greatly extend the transmission distance and providing PoE at the same time. It is for example a perfect, inexpensive and time saving solution for security cameras.

Extend an existing PoE connection over the 100m distance limit

- Ethernet Speed: 10/100/1000Mbps Gigabit Half/Full Duplex
- PoE Standard: IEEE802.3af / IEEE802.3at
- Transmission range up to 500 m (by cascading)
- Cascadable up to 3 extender (af.) and up to 4 extender (at.)
- Plug-and-Play Installation - No configuration necessary

- Maximum power output: 22 Watts
- Status LEDs on the device (Power Indicator and Network indicator)
- Circuit isolation protection
- Fixing points for wall installation
- Pin Feet PoE Input: Both 1/2 (-), 3/6 (+) and 7/8 (-), 4/5 (+)
- Pin Feet PoE Output: 1/2 (-), 3/6 (+)
- Operating Temperature: -10 to 45°C
- Dimensions (L x W x H): 127 mm x 47 mm x 37 mm
- Weight: 140g
- Color: Black

Attributes

- Industrial usage: no

Package contents

- PoE+ Extender
- Manual

| Logistics | | | | | | |
|------------------------------|--------------|-------------|------------|------------|-------------|-----------------|
| | Number (pcs) | Weight (kg) | Depth (cm) | Width (cm) | Height (cm) | cm ³ |
| Packaging Unit Carton | 100 | 15.00 | 29.50 | 49.00 | 28.00 | 40,474.00 |
| Packaging Unit Inside | 1 | 0.15 | 5.50 | 13.50 | 4.50 | 334,125.00 |
| Packaging Unit Single | 1 | 0.15 | 5.50 | 13.50 | 4.50 | 334,125.00 |
| Net single without Packaging | 0 | 0.14 | 4.70 | 12.70 | 3.70 | 220,853.00 |

More images:



