

DIGITUS 16 Port 10G Ethernet PoE+ Injector, 802.3at, 250 W

DN-95116
EAN 4016032430377



10G Ethernet PoE+ Injector Hub, 802.3at 16-port, Power Pins:3/6(+), 1/2(-), 250W

The DIGITUS® DN-95116 is an 16 port 10G PoE+ mid-span hub (PoE injector). It offers 16 input ports for data and 16 output ports which make data and PoE available. Each PoE-port supports connected devices in accordance with the IEEE802.3af and IEEE802.3at PoE standard with 15.4 watts and/or 30 watts, such as PoE access points, PoE IP-telephones or PoE IP cameras, for example. The switch makes available a maximum budget of 250 watts for all ports and maximum budget of 30 watts per port.

Minimization of the cabling costs for PoE-capable devices

- 32 x 10/100/1000Mbps/2.5G/10G (16 x input data, 16 x output data+PoE)
- Compatible with the IEEE802.3af and IEEE802.3at standards
- PoE power supply via PIN 1.2(V-) and PIN 3.6(V+)
- Maximum total output of 250 watts
- Compatible with IEEE802.3, IEEE802.3u and IEEE802.3ab standards
- Automatic cable recognition - Auto-MDI-/ MDI-X function

- Auto recognition of full and half duplex
- Power supply: 100V AC ~ 240V AC
- Operating temperature range: 0 °C to 40 °C
- Storage temperature: -20°C - 70°C
- Dimensions (mm): 440(L) x 200(W) x 45(H)
- MTBF: 100,000 hours
- Power consumption: 15W
- Number of ports: 16
- PoE Power budget: 250 W
- PoE standard: IEEE802.3at (PoE+)
- Ethernet speed: 10 gigabit
- Industrial usage: no

Package contents

- 16 port 10G PoE+ injector
- Quick start guide
- Power Cord cable
- Mounting accessories

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	5	20.83	59.50	29.50	22.00	0.00
Packaging Unit Inside	1	4.17	50.00	28.00	10.00	0.00
Packaging Unit Single	1	4.17	50.00	28.00	10.00	0.00
Net single without Packaging	0	2.80	44.00	20.00	4.50	0.00

More images:

