

DIGITUS HP-compatible SFP+ 10G MM 850nm 300m with DDM

DN-81200-01
 EAN 4016032446149



10G SFP+ Module, Multimode, DDM, HP-compatible LC Duplex Connector, 850nm, up to 300m, HP

The DIGITUS® mini GBIC (SFP) transceiver modules offer highest quality and reliability. Whether from switch to switch, converter to switch, converter to converter or any else application: The wide product range of DIGITUS® modules makes possible a flexible usage of the fiber technology. The conformity to the MSA (Multi Source Agreement) standard ensures a compatibility to third party manufacturers.

The plug and play fiber connection

- Mini GBIC SFP (Small Form Factor Pluggable) module
- Supports DDM (Digital Diagnostic Monitoring)
- High quality and excellent reliability
- 10 Gbps Maximum Data Rate
- Compliant to IEEE802.3ae 10 Gigabit Standard
- Class 1 laser product compliant with EN 60825-1
- Easy plug-and-play installation
- MSA (Multi Source Agreement) compliant
- Hot pluggable
- Connector: 1x LC Duplex
- Wavelength: 850nm

- Transmission Power: Minimum -5 dBm, Maximum -1 dBm
- Empfangssensitivität: Minimum -11,5 dBm
- For a distance of up to 0.3km
- Safe fast-locking mechanism
- 3.3V power supply
- Operating temperature: 0 °C ~ 70 °C
- Compatible with the following manufacturers: Allied Telesis, Allnet, Avaya, CISCO, D-Link, Edimax, FINISAR, FORCE 10, Gigamon, Intellinet, KTI Networks, Level One, PLANET, Tenda, TP-Link, TRENDnet, Mikrotik, ENTERASYS, RIVERSTONE, Unifi, Ubiquiti, ZyXEL, ZTE
- Mode: Multimode
- Connector: LC
- Distance (km): 0.3
- Wavelength: 850 nm
- DDM Support: yes
- Broadcasting Mode: Unidirectional
- Manufacturer compatibility: Universal (MSA)
- Ethernet speed: 10 Gigabit

Package contents

- SFP module

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	20	0.80	41.00	26.00	16.00	17,056.00
Packaging Unit Inside	1	0.04	3.00	11.50	9.00	310.50
Packaging Unit Single	1	0.04	3.00	11.50	9.00	310.50
Net single without Packaging	0	0.03	5.50	1.20	0.80	5.28

More images:



SFP Modules							
Part Number	Data Rate	Speed	Distance	Connector	Wavelength	Operating Temperature	Industrial Model
Fast Ethernet							
DS-4910	4000000000	10 Gbps	10km	LC	1310nm	0 to 70 °C	✓
DS-4914	4000000000	10 Gbps	10km	LC	1550nm	0 to 70 °C	✓
DS-4918	4000000000	10 Gbps	10km	LC	1550nm	0 to 70 °C	✓
10 Gigabit							
DS-4920	4000000000	10 Gbps	10km	LC	1310nm	0 to 70 °C	✓
DS-4924	4000000000	10 Gbps	10km	LC	1550nm	0 to 70 °C	✓
DS-4928	4000000000	10 Gbps	10km	LC	1550nm	0 to 70 °C	✓
DS-4932	4000000000	10 Gbps	10km	LC	1550nm	0 to 70 °C	✓
DS-4936	4000000000	10 Gbps	10km	LC	1550nm	0 to 70 °C	✓
100 Gbps							
DS-4940	40000000000	100 Gbps	10km	LC	1310nm	0 to 70 °C	✓
DS-4944	40000000000	100 Gbps	10km	LC	1550nm	0 to 70 °C	✓
Fast Ethernet							
DS-4910	4000000000	10 Gbps	10km	LC	1310nm	0 to 70 °C	✓
DS-4914	4000000000	10 Gbps	10km	LC	1550nm	0 to 70 °C	✓
DS-4918	4000000000	10 Gbps	10km	LC	1550nm	0 to 70 °C	✓
DS-4920	4000000000	10 Gbps	10km	LC	1310nm	0 to 70 °C	✓
DS-4924	4000000000	10 Gbps	10km	LC	1550nm	0 to 70 °C	✓
DS-4928	4000000000	10 Gbps	10km	LC	1550nm	0 to 70 °C	✓
DS-4932	4000000000	10 Gbps	10km	LC	1550nm	0 to 70 °C	✓
DS-4936	4000000000	10 Gbps	10km	LC	1550nm	0 to 70 °C	✓