

DIGITUS Direct Attach Cable 40G QSFP+ to 4XSFP+ 1m

DN-81321
EAN 4016032484981



Cavo DAC breakout 1 m da 1x 40G a 4x 10G da 1x 40G a 4x 10 G

I cavi DAC breakout DN- 81321 da QSFP+ a 4x SFP+ sono ottimizzati per l'uso nei centri di calcolo. Soddisfano la crescente domanda di una maggiore densità di canali con un'elevata integrità del segnale nell'informatica ad alte prestazioni, nei core switch e nei sistemi NAS.

Fino a velocità dati 10.3125Gbps per canale, trasferimento fino a 5m, temperatura operativa: 0~70, singola alimentazione +3.3V

- Velocità di trasmissione dati del canale 10,3125 Gbps
- Temperatura di esercizio da 0 a + 70°C
- Temperatura di stoccaggio da -40 a + 85°C
- Tensione di alimentazione 3,3 V nominale

- Interfaccia: connettore a 38 pin (QSFP+)
- Connettore a 20 pin (SFP+)
- Interfaccia di gestione Seriale, I2C
- Lunghezza del cavo: 3 m
- Compatibile con i seguenti produttori: Allnet, CISCO, 3COM, D-LINK, Dell, Edimax, Etherwan, ENTERASYS, EXTREME, FINISAR, FORCE 10, Fortinet, HUAWEI, IBM, JUNIPER, LINKSYS, NETGEAR, NORTEL, RIVERSTONE, ZTE, ZYXEL
- Supporto DDM: no

Package contents

- Cavo DAC breakout da 40G QSFP+ a 4XSFP+ 1m

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm ³
Packaging Unit Carton	0	0.00	0.00	0.00	0.00	0.00
Packaging Unit Inside	0	0.00	0.00	0.00	0.00	0.00
Packaging Unit Single	0	0.00	0.00	0.00	0.00	0.00
Net single without Packaging	0	0.00	0.00	0.00	0.00	0.00

More images:



