

DIGITUS Direct Attach Cable 40G QSFP+ to 4XSFP+ 3m

DN-81323
EAN 4016032484998



Cavi breakout DAC 3 m da 1x 40G a 4x 10G da 1x 40G a 4x 10 G

I cavi DAC breakout DN- 81321 da QSFP+ a 4x SFP+ sono ottimizzati per l'uso nei centri di calcolo. Soddisfano la crescente domanda di una maggiore densità di canali con un'elevata integrità del segnale nell'informatica ad alte prestazioni, nei core switch e nei sistemi NAS.

Fino a velocità dati 10.3125Gbps per canale, trasferimento fino a 5m, temperatura operativa: 0~70°, singola alimentazione +3.3V

- Velocità di trasmissione dati del canale 10,3125 Gbps
- Temperatura di esercizio da 0 a + 70°C
- Temperatura di stoccaggio da -40 a + 85°C
- Tensione di alimentazione 3,3 V nominale

- Interfaccia: connettore a 38 pin (QSFP+)
- Connettore a 20 pin (SFP+)
- Interfaccia di gestione Seriale, I2C
- Lunghezza del cavo: 3 m
- Compatibile con i seguenti produttori: Allnet, CISCO, 3COM, D-LINK, Dell, Edimax, Etherwan, ENTERASYS, EXTREME, FINISAR, FORCE 10, Fortinet, HUAWEI, IBM, JUNIPER, LINKSYS, NETGEAR, NORTEL, RIVERSTONE, ZTE, ZYXEL
- Supporto DDM: no

Package contents

- Cavo DAC breakout da 40G QSFP+ a 4XSFP+ 3m

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm ³
Packaging Unit Carton	80	15.00	48.00	48.00	38.00	87,552.00
Packaging Unit Inside	1	0.18	0.00	0.00	0.00	0.00
Packaging Unit Single	1	0.18	26.00	26.00	3.00	2,028.00
Net single without Packaging	0	0.34	5.80	1.40	1.30	10.55

More images:



