

# DIGITUS Cat.6A U/FTP installation cable, 500 m, duplex, Cca

DK-1625-A-VH-D-5  
EAN 4016032486787



### CAT 6A U-FTP installation cable, 500 MHz Cca (EN 50575), AWG 23/1, 500 m drum, dx, blue

The Digitus® Cat.6A U/FTP installation cable is characterized by the following cable construction 4x2x AWG23/1 and reaches a transmission frequency up to 500 MHz. The halogen free cable jacket is conform to the standard IEC 60332-1, FRNC-B, LSZH-1 and CPR Euro class Cca. The cable is suitable for building structured cabling in the secondary and tertiary area. Compliant with the following standards ISO/IEC 11801, DIN EN 50173, DIN EN 50288-10-1.

#### Future-oriented standards and high-end quality for your network.

- Physical properties:
- Conductor: Bare annealed copper, solid AWG 23/1
- System/s of AVCP: AVCP 3
- Total number of insulated conductors: 8, twisted in 4 pairs
- Color code: Blue-white, orange-white, green-white, brown-white
- Individual pair shielding: Aluminum foil, providing 100 % coverage
- Overall shielding: None, with drain wire
- Outer sheath: Eca to B2ca acc. to EN 50575; LSZH
- Outer sheath color: Light blue (RAL 5012)
- Mechanical properties:
- Tensile loading: 150N max.
- Dynamic bending radius: 8x AD mm min.
- Static bending radius: 4x AD mm min.
- Shipping- and storage temperature range: -20 °C up to +60 °C
- Operating temperature range: -20 °C up to +75 °C

- Installation temperature range: 0 °C up to +50 °C
- Overall diameter Simplex (nominal): 7.0 (Eca); 7,2 mm (Dca); 7,6 mm (Cca); 7,6 mm (B2ca)
- Weight (kg/km): 56 kg (Eca); 57 kg (Dca); 58 kg (Cca); 58 kg (B2ca)
- Electrical properties:
- Impedance: 100±15 Ohm @ 4 - 100MHz; 100±25 Ohm @100-500 MHz
- Capacitance: 45 pF/m nominal @ 1 KHz
- Capacitance unbalance (pair-ground): 1.6 pF/m max. @ 1 KHz
- Insulation resistance: 5 GOhm x km min.
- DC loop resistance: 190 Ohm/km max. (2% max. resistance unbalance)
- Voltage resistance: 72 Vdc max.
- Coupling attenuation: CA-Type 2
- Signal propagation delay: 450 nS/100 m max.
- Propagation delay: 15 nS/100 m max.
- Separating class: "c" acc. to EN 50174-2
- NVP: 70%
- Assortment: Twisted Pair Installation Cables
- Category: CAT 6A
- Shielding: U-FTP, pairs in metal foil
- CPR: Cca
- Length: 500 m
- Color: light-blue
- Jacket: LSOH
- Structure: 4 x 2 AWG 23/1, solid twisted pair

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	1	0.00	0.00	0.00	0.00	0.00
Packaging Unit Inside	1	0.00	0.00	0.00	0.00	0.00
Packaging Unit Single	1	0.00	0.00	0.00	0.00	0.00
Net single without Packaging	0	0.00	0.00	0.00	0.00	0.00

More images:

Category	Shielding	Performance Class	Shielding Class	Shielding Type
B2+	Shielded	Very High	1+	Shielded
C6a	Shielded	High	3	Shielded
D6a	Shielded	Medium	3	Shielded
E6a	Shielded	Low	3	Shielded

Category	Shielding	Performance Class	Shielding Class	Shielding Type
B2+	Shielded	Very High	1+	Shielded
C6a	Shielded	High	3	Shielded
D6a	Shielded	Medium	3	Shielded
E6a	Shielded	Low	3	Shielded

Category	Shielding	Performance Class	Shielding Class	Shielding Type
B2+	Shielded	Very High	1+	Shielded
C6a	Shielded	High	3	Shielded
D6a	Shielded	Medium	3	Shielded
E6a	Shielded	Low	3	Shielded

**CAT 6a U/FTP Installation Cable, 500m, Simplex, E<sub>ca</sub>**

- AWG 23/1
- 500 MHz
- 10 Gbit/s
- CAT 6a
- E<sub>ca</sub> CPR class
- 20°/+75°
- LSZH