

# DIGITUS 8K HDMI Splitter, 1x4

**DS-55340**  
**EAN 4016032495611**



**1x4 HDMI Splitter, 8K/60Hz (4:4:4), Toslink, Stereo, EDID Control**

The HDMI Splitter from DIGITUS® distributes/mirrors audio and video signals from your HDMI device to 4 TVs, monitors or projectors in a resolution of UHD 8K/60Hz. Audio signals can also be decoupled via Toslink or 3.5 mm stereo connection and played back separately. The EDID switch can be used to make settings to match the connected displays.

**The HDMI Splitter from DIGITUS® distributes/mirrors audio and video signals from your HDMI device to 4 televisions, screens or projectors with a maximum resolution of 8K/60Hz**

- Distributes an HDMI signal to 4 TVs/monitors/projectors
- Audio extractor: Toslink / stereo (3.5 mm) - decoupling and separate playback of the audio signal
- EDID switch / management
- Max. Resolution: 8K/60Hz (4:4:4)
- Video bandwidth: 48 Gbps
- Supports High Dynamic Range (HDR)
- Supports HDCP 2.3
- Supports Deep Color (36 bit)
- HDMI 2.1
- Connections:
- 1x HDMI input (8K/60Hz)
- 4x HDMI output (8K/60Hz)

- 1x Toslink
- 1x 3.5 mm audio
- 1x DC / 5V input - power supply connection
- 5x status LEDs
- 1x EDID switch
- 1x Micro USB input - Service
- Operating temperature: 0-70°
- Power consumption: approx. 7W
- Housing: Metal
- Dimensions (housing): L 18.8 x W 7.1 x H 1.8 cm
- Weight: 285 g
- Color: black

**Attributes**

- HDTV Resolution max.: 7680 × 4320 Pixel, 60Hz
- HDTV Standard: Ultra HD 8K
- Number of ports: 4
- Signal input: HDMI
- Signal output: HDMI
- Video connection ports: HDMI

**Package contents**

- 1x HDMI Splitter
- 1x power supply unit (5V/2A, 1.2 m)
- 1x QIG

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	20	12.40	39.50	30.50	44.00	53,009.00
Packaging Unit Inside	1	0.62	0.00	0.00	0.00	0.00
Packaging Unit Single	1	0.62	20.70	18.70	5.60	2,167.70
Net single without Packaging	0	0.28	18.80	7.10	1.80	0.00

More images:

