

DIGITUS USB-C docking station, 13-port

DA-70918

EAN 4016032497776



USB-C Docking Station, 13-Port, 3x HDMI, 2x DP 4x USB-A, 1x USB-C, 1x RJ45, 1x DC, 1x Audio

Expand your workplace with 13 additional connection options and take advantage of the wide range of connectivity options. The dock enables dual or triple monitor setups (4K/60Hz on all monitors) in MST mode (screen extension) for Windows, macOS (including M1, M2, M3 chipsets), ChromeOS and Linux PCs. Choose from 3x HDMI or 2x DisplayPort connections and combine them as you wish. Benefit from ultra-fast data transfers thanks to 3x USB-A 3.2 Gen 1 (5 Gbit/s), 1x USB-A 3.2 Gen 2 (10 Gbit/s) and 1x USB-C 3.2 Gen 2 (10 Gbit/s) ports, some of which also support charging mobile devices at 1.5A. A Gigabit Ethernet connection (RJ45) with 2500 Mbit/s ensures a perfect network connection. The supplied power supply unit (21V/7.1A, 150W) provides the docking station and the notebook with sufficient power during use. The 3.5 mm audio jack and the reversible 100 cm USB-C 3.2 Gen 2 connection cable offer additional flexibility. The docking station supports DP 1.4 Alt Mode (backwards compatible with DP 1.2), HDR and HDCP 2.2/1.4. Please note that a manual installation of drivers (DisplayLink) for your operating system is required to use the full functionality (dual/triple monitor and audio) of the dock.

Our 13-port USB-C docking station expands the connection options for notebooks and offers a complete solution for the entire workplace

- Connections:
- 1x USB-C (3.2 Gen 2) input + 1x reversible USB-C 3.2 Gen 2 connection cable (100 cm) - Flexible connection to the host PC
- 3x HDMI port + 2x DP port output - Max. Resolution: UHD (4K/60Hz)
- 3x USB-A 3.2 Gen 1 connection - 5 Gbit/s data transfer & charging function: 7.5W (5V/1.5A), 1x 4.5W (5V/0.9A), 1x 4.5W (5V/0.9A)
- 1x USB-A 3.2 Gen 2 port - 10 Gbit/s data transfer & charging function: 1x 7.5W (5V/1.5A)
- 1x USB-C 3.2 Gen 2 connection - 10 Gbit/s data transfer & charging function: 1x 7.5W (5V/1.5A)
- 1x RJ45 Gigabit Ethernet connection - 10/100/1000/2500 Mbit/s bandwidth
- 1x DC-Jack - 150 watts max. (96W host, 54W dock)
- 1x 3.5 mm audio jack
- Theft protection - 1x Standard + 1x Nano
- Chipset information: DL-6950-N, NT5CC256M16ER-EK, VL171, VL103R-Q4, VL822T, VL162, VL817-Q7S, RTL8156BG-CG, PS186
- Supports DP 1.4 Alt Mode, backwards compatible with DP 1.2 Alt Mode (DisplayPort Alternate Mode) and DisplayLink
- Supports HDCP 2.2, HDCP 1.4
- Supports HDR (High Dynamic Range)
- Short-circuit, overcurrent and overvoltage protection

- Product color: Grey / Black
- Housing: aluminum / plastic
- Weight: 446.5 g
- Dimensions: L 22.5 x W 8.5 x H 2.5 cm
- Operating temperature : 0°C - + 45°C
- Cable length: 100 cm
- Cable color: Black
- Power switch with LED display
- Notes:
- Please note that a manual installation of drivers for your respective operating system (Windows, MacOS, ChromeOS, Android, Linux) is necessary
- Please use the following link to install the latest DisplayLink driver: <https://www.synaptics.com/products/displaylink-graphics>
- Not all USB-C ports support all functions of the USB-C standard. Make sure that the USB-C port on your notebook supports DisplayPort Alternate Mode (DP-Alt Mode) and USB Power Delivery (PD)
- Supports dual monitor (2x 4K/60Hz) & triple monitor (3x 4K/60Hz) in MST mode (Multi Stream Transport / extend screen) - Windows, macOS, ChromeOS, Linux
- Supports dual monitor (2x 4K/60Hz) & triple monitor (3x 4K/60Hz) in SST mode (single stream transport / screen mirroring) - Windows, macOS, iOS, iPadOS, Android, ChromeOS, Linux
- Supports Dual Monitor & Triple Monitor (MST - expand screen) - also with Apple computers with M1, M2, M3 chipsets
- The video output capability (actual resolution) depends on the graphics card of your notebook, the connected monitor and the DP mode
- To use the full range of functions, the notebook must support DP 1.4 Alt Mode
- The docking station is not operational without a connected power supply (DC jack)
- Compatibility exists with the following operating systems up to their current versions: From Windows 7, from macOS 12, from iPhone 15 (iOS) , from iPadOS 16, from Android 14, from ChromeOS 116.0.5845.120, from Linux 22.04 LTS

Attributes

- HDTV Resolution max.: 3840 x 2160 Pixel, 60Hz
- LAN connector (RJ45): yes
- Card reader: no
- Number of audio ports: 1
- Number of display ports: 3
- Number of network ports: 1
- Number of USB A ports: 4
- Number of USB-C ports: 1

- Number of video ports: 5
- Video connection ports: HDMI, HDMI, HDMI, DisplayPort, DisplayPort

- 1x USB-C docking station, 13-port
- 1x QIG
- 1x USB-C cable (100 cm)
- 1x power supply unit (21V/7.1A ; 120 cm)
- 1x power cable (100 cm)

Package contents

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm ³
Packaging Unit Carton	10	9.00	27.00	42.00	31.50	35,721.00
Packaging Unit Inside	1	0.90	0.00	0.00	0.00	0.00
Packaging Unit Single	1	0.90	30.00	13.00	8.20	3,198.00
Net single without Packaging	0	0.44	22.50	8.50	2.50	0.00

More images:



