

Planet SFP-Port 100Base-BX Transceiver (WDM, TX:1550nm, BiDi LC, Single-Mode) -20km

MFB-FB20
EAN 4711213687051



Planet SFP Module, 100 Mbps WDM Singlemode, LC Simplex, 20km, Tx 1550 WDM, TX:1550nm, 20km

The MFB family SFP Fast Ethernet transceivers can be installed in Switch and Media Converter products with 100Base-BX SFP interface. The MFB family SFP Fast Ethernet transceivers are hot-pluggable and hot-swappable. You can plug in and pull out the transceivers to / from any SFP port without having to power off the Switch / Media Converter.

For distances up to 20 km on a Single-Mode fiber

- SFP Multi-Source Agreement compliant
- 125Mbps IEEE 802.3u 100Base-FX compliant
- Industry standard small form pluggable (SFP)
- 125Mbps FDDI ISO / IEC 9314-1 compliant
- Serial ID functionality support
- AC-coupled differential inputs and outputs

- Class 1 laser safety standard IEC 825 compliant
- 20 km link on a Single-Mode fiber
- Connector: WDM / LC bidirectional
- Wavelength: TX: 1550nm, RX: 1310nm
- Operating temperature: 0 to 60°C
- Mode: Singlemode
- Connector: LC
- Distance (km): 20
- Wavelength: 1550/1310 nm
- DDM Support: no
- Broadcasting Mode: Bidirectional
- Manufacturer compatibility: Universal (MSA)
- Ethernet speed: Fast Ethernet

Package contents

- SFP-Port 100Base-BX Transceiver, Single-Mode

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm ³
Packaging Unit Carton	1	0.06	12.50	7.00	2.50	218.75
Packaging Unit Inside	1	0.06	12.50	7.00	2.50	218.75
Packaging Unit Single	1	0.06	12.50	7.00	2.50	218.75
Net single without Packaging	0	0.06	12.50	7.00	2.50	218.75