

# Planet Industrial 8 Port Gigabit Switch, Managed, 2 Uplinks

IGS-10020MT  
EAN 4711213688782



## Planet IP30 Industrial Switch, 8 x Gigabit, 2 x SFP, -40/+75°C, Managed

IP30 industrial enclosure for DIN rail mounting, 8 x 10/100/1000 Mbps (RJ45), Auto MDI/MDI-X, 2 x SFP slots for MGB and MFB modules, operating temperature -40 to +75°C, DC power supply optional, Web Management

### IPv6 / IPv4 full-functioned secure switch for building automation networking

- 8-Port 10/100/1000Base-T RJ-45 copper interface
- 2x 100/1000BASE-X mini-GBIC/SFP slots, SFP type auto detection
- Prevents packet loss with back pressure (Half-Duplex) and IEEE 802.3x PAUSE frame flow control (Full-Duplex)
- Storm Control support (Multicast, Unknown-Unicast)
- Supports VLAN (IEEE 802.1Q Tagged VLAN, up to 255 VLANs groups, out of 4045 VLAN IDs, Provider Bridging (VLAN Q-in-Q) support (IEEE 802.1ad), Private VLAN Edge (PVE), Protocol-based VLAN, MAC-based VLAN, Voice VLAN)

- Supports Spanning Tree Protocol (STP, IEEE 802.1D, RSTP, IEEE 802.1w, MSTP, IEEE 802.1s, BPDU Guard)
- Supports Link Aggregation (802.3ad Link Aggregation Control Protocol (LACP), Cisco ether-channel (Static Trunk), maximum 5 Trunk groups, up to 10 ports per Trunk group, up to 20Gbps bandwidth (Duplex Mode)
- Provides port mirror (many-to-1)
- -40 to 75 °C operating temperature
- Number of ports: 8
- Ethernet speed: Gigabit
- Industrial usage: yes
- Installation type: DIN rail
- Managed: yes
- Number of ports (Uplink): 2
- Outdoorsuitable: no
- PoE (Power over Ethernet): no
- Protection against vanadism: no
- Uplink port connection: SFP
- VLAN: yes

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm <sup>3</sup>
Packaging Unit Carton	1	0.94	13.00	7.00	2.00	182.00
Packaging Unit Inside	1	0.94	13.00	7.00	2.00	182.00
Packaging Unit Single	1	0.94	13.00	7.00	2.00	182.00
Net single without Packaging	0	0.94	13.00	7.00	2.00	182.00

More images:

