

Planet 24 Port Gigabit Switch, 19 Inch, Managed, 4 Uplinks

MGSW-28240F
EAN 4711213689666



Planet Metro L3 Switch, 24xSFP, 4xSFP+ 10G, 4xRJ45, AC+DC, -10/+60°C, Managed

New version (V3) with Layer 3 routing (OSPFv2, static) and ERPS ring. 19 inch Ethernet Gigabit Switch with 24 x SFP Slots 100/1000 Mbps for FO Modules (MFB/MGB), 4 x SFP+ Slots 10GbE, 4 x 10/100/1000 RJ45 (shared), 1U, DI/DO (2 x Digital Input, 2 x Digital Output) for sensors and alarm systems, redundant power supply, 1 x internal power supply 100-240V AC, 2 x connector for an external power supply 36-60V DC, power consumption max. 39 Watt, IPv4/6, SNMP, SSH, Console, SSL Web Management with extensive L2/L4 functions like VLAN, Storm Control, LACP, Spanning Tree (STP, RSTP, MSTP), QoS, IGMP Snooping, RMON, LLDP, ACL, RADIUS/TACACS+, etc. Dimensions 440 x 200 x 44.5 mm, weight 2.9kg

Best solution for all long-reach applications

- 24-port 100/1000Base-X SFP mini-GBIC slot
- 4 shared 10/100/1000Base-T RJ-45 ports
- 4-port 1G/10G SFP+ slot
- RS-232 RJ45 console interface for switch basic management and setup
- -10 to 60 °C operating temperature
- 19-inch rack-mountable

- Prevents packet loss with back pressure (Half-Duplex) and IEEE 802.3x PAUSE frame flow control (Full-Duplex)
- Storm Control support (Broadcast/ Multicast/ Unknown-Unicast)
- Supports VLAN (IEEE 802.1Q Tagged VLAN, Provider Bridging (VLAN Q-in-Q) support (IEEE 802.1ad), Protocol VLAN, Voice VLAN, Private VLAN, Management VLAN, GVRP)
- Supports Spanning Tree Protocol (STP, IEEE 802.1D, RSTP, IEEE 802.1w, MSTP, IEEE 802.1s, BPDU Guard)
- Supports Link Aggregation (802.3ad Link Aggregation Protocol (LACP), Cisco ether-channel (Static Trunk), maximum 12 trunk groups, up to 16 ports per trunk group, up to 32Gbps bandwidth (Duplex Mode))
- Number of ports: 24
- Ethernet speed: Gigabit
- Industrial usage: no
- Installation type: 19 inch, Desktop
- Managed: yes
- Number of ports (Uplink): 4
- Outdoorsuitable: no
- PoE (Power over Ethernet): no
- Protection against vandalism: no
- Uplink port connection: SFP
- VLAN: yes

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	1	3.82	55.50	30.50	9.50	16,081.10
Packaging Unit Inside	1	3.82	55.50	30.50	9.50	16,081.10
Packaging Unit Single	1	3.82	55.50	30.50	9.50	16,081.10
Net single without Packaging	0	3.82	55.50	30.50	9.50	16,081.10

More images:

