

# Planet 16-Port 10/100/1000T 802.3at PoE + 2-Port Gigabit SFP Ethernet Switch with LCD PoE Monitor (300W)

GSW-2620VHP  
EAN 4711605282109



## 24-Port 10/100/1000T 802.3at PoE Switch + 2-Port Gigabit SFP and LCD Monitor for PoE,

Commutateur Gigabit Ethernet 26 ports 19U 1U avec affichage pour une surveillance rapide des informations d'état utiles. 24 x 10/100/1000 (RJ45) avec PoE + 803.at Injecteur, compatible 802.3af, 2 x SFP Slots 100/1000 Mbps, PoE Puissance Budget 300 Watt. Il est possible d'activer / désactiver le VLAN (isolement) sur port via un commutateur DIP, ainsi qu'un mode PoE spécial qui permet une portée de 250 mètres (À 10 Mbps) au lieu de 100 mètres (avec 1000 Mbps). Consommation max. 330 watts. Comprend un support de montage de 19 pouces. Poids 3,4kg, dimensions 233 x 440 x 44 mm.

### LCD Monitor for Real-time PoE Usage and System Status Display

- Hardware-based 10/100/1000Mbps auto-negotiation and auto MDI/MDI-X
- Flow control for full duplex operation and back pressure for half duplex operation
- 9216bytes packet size
- Integrates address look-up engine, supporting 8K absolute MAC addresses
- IEEE 802.1Q VLAN transparency
- Automatic address learning and address aging
- 19-inch desktop size, 1U height, rack mountable
- LED indicators for system power, per port PoE ready and PoE activity, speed, Link/Act
- 3 silent fans to provide stable and efficient power performance
- Supports Energy-Efficient Ethernet (EEE) function (IEEE 802.3az)
- Supports contact discharge of ±6KV DC and air discharge of ±8KV DC for Ethernet ESD protection
- Supports ±6KV surge immunity

- PoE Standard: IEEE 802.3af Power over Ethernet/PSE, IEEE 802.3at Power over Ethernet Plus/PSE
- PoE Power Output: Per port 53V-54V DC, 300mA. max. 15.4 watts (IEEE 802.3af), Per port 53V-54V DC, 600mA. max. 30 watts (IEEE 802.3at)
- Power Pin Assignment: 1/2 (+), 3/6 (-)
- PoE Power Budget: 300 watts
- Max. Number of Class 2 PDs: 24
- Max. Number of Class 3 PDs: 23
- Max. Number of Class 4 PDs: 11
- Operating Temperature: -10 ~ 60 degrees C
- Storage Temperature: -10 ~ 70 degrees C
- Nombre de ports: 24
- Budget d'alimentation PoE: 300 W
- Norme PoE: IEEE802.3at (PoE+)
- Vitesse Ethernet: Gigabit
- Puissance de sortie: 24 W
- Utilisation industrielle: Non
- Adapté pour un usage en extérieur: Non
- Connexion du port uplink: SFP
- Managed: Non
- Nombre de ports (uplink): 2
- PoE (Power over Ethernet): Oui
- Protection contre le vandalisme: Non
- Type d'installation: 19 pouces
- VLAN: Oui

### Package contents

- 24 Port PoE Switch GSW-2620VHP
- Power Cable
- Installation Material
- Manual

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm <sup>3</sup>
Packaging Unit Carton	1	0.00	0.00	0.00	0.00	0.00
Packaging Unit Inside	1	0.00	0.00	0.00	0.00	0.00
Packaging Unit Single	1	0.00	0.00	0.00	0.00	0.00
Net single without Packaging	0	3.40	44.00	23.30	4.40	4,510.88