

Planet 19 Inch POE+ Switch, 802.3at, 20xRJ45 Gigabit, 4xSFP, Managed, 220 Watt

GS-4210-16P4C
EAN 4711605282215



Planet 19 Inch POE+ Switch, 802.3at, 20xRJ45 Gigabit, 4xSFP, Managed, 220 Watt

20 port Gigabit Ethernet Switch 19 inch 1U, 20 x 10/100/1000 (RJ45), including 16 with PoE+ 802.3at injector, compatible with 802.3af, 4 x SFP slots for MFB/MGB modules (100/1000 Mbps). PoE Power Budget 220 watts (at 25°C) resp. 190 watts (at 50°C). Extensive functions, e.g. VLAN, LACP, QoS, IGMP Snooping, ACL, RSTP, LLDP and more. Web / Telnet / Console Management, IPv4/IPv6, SNMP. Power consumption max. 251 watts. Including 19 inch mounting bracket. Weight 4132g, dimensions 440 x 300 x 44.5 mm.

- 16-Port 10/100/1000T 802.3at PoE + 4-Port Gigabit TP/SFP Combo Managed Switch/220W
- Supported standards: IEEE 802.3x Full-duplex and Flow Control, IEEE 802.3ad Trunk (Link Aggregation), IEEE 802.3af Power over Ethernet (PoE), IEEE 802.1Q VLAN, IEEE 802.1p Class of Service, IEEE 802.1d Spanning Tree Protocol

- Advanced store-and-forward packet switching ensures an optimized data transfer
- Supports port configuration, port mirroring, bandwidth control, broadcast storm control
- PoE on/off setting via Web management
- VLAN setting port-based 32 groups / tag-based: 26 groups
- Trunk setting 3 groups (1 - 4 port for each group)
- QoS-Support
- Supports MAC address filtering, TCP/UDP filtering
- Industrial usage: no
- Managed: no
- Outdoorsuitable: no
- PoE (Power over Ethernet): no
- Protection against vanadism: no
- VLAN: no

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	2	10.80	59.00	21.00	42.00	52,038.00
Packaging Unit Inside	1	5.40	0.00	0.00	0.00	0.00
Packaging Unit Single	1	5.40	0.00	0.00	0.00	0.00
Net single without Packaging	0	5.40	0.00	0.00	0.00	0.00

More images:

