

Planet Industrial 4 Port Gigabit Switch, Managed, 2 Uplinks

IGS-5225-4T2S
EAN 4711605282406



Planet Industrial Gigabit Switch, DIN Rail, 4xRJ45, 2xSFP, -40/+75°C, Managed

6 Port Gigabit Ethernet Switch, fanless IP30 Industrial housing for DIN rail mounting, also suitable for wall mounting, 4 x RJ45 10/100/1000 Mbps, Auto MDI/MDI-X, 2 x SFP slots 100/1000 (for MFB and MGB Modules), operating temperature -40 to + 75°C, ESD protection 5KV DC, power consumption max. 8.5 watt, redundant current inputs 12-48V DC and 24V AC, power supply not included. Extensive features, e.g. Modbus TCP, VLAN, LACP, Redundant Ring (STP, RSTP, MSTP, G.8032 ERPS), QoS, Multicast, IGMP Snooping, Static Layer 3 Routing, ACL, IPv4 / IPv6, Web Management, Console (Serial RJ45), SNMP and much more. Very compact dimensions of only 32x87x135 mm, weight

456 grams.

- Number of ports: 4
- Ethernet speed: Gigabit
- Industrial usage: yes
- Installation type: DIN rail
- Managed: yes
- Number of ports (Uplink): 2
- Outdoorsuitable: no
- PoE (Power over Ethernet): no
- Protection against vandalism: no
- Uplink port connection: SFP
- VLAN: yes

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm ³
Packaging Unit Carton	15	10.05	41.00	35.00	34.00	48,790.00
Packaging Unit Inside	1	0.67	20.00	14.00	9.00	2,520.00
Packaging Unit Single	1	0.67	20.00	14.00	9.00	2,520.00
Net single without Packaging	0	0.67	20.00	14.00	9.00	2,520.00

More images:

