

Planet Industrial Switch, 8 x RJ45, 100 Mbps, -40/+75°C, Compact & Efficient

ISW-800T
EAN 4711605282802



Planet Industrial Switch, 8 x RJ45, 100 Mbps, -40/+75°C, Compact & Efficient

Very energy-saving and compact! 8 Port Ethernet Switch, IP30 industrial housing for DIN rail mounting (DIN Rail), also suitable for wall mounting, 8 x RJ45 10/100Base-TX, Auto MDI/MDI-X, operating temperature -40 up to +75°C, ESD protection, redundant current inputs 12-48V DC and 24V AC, delivery without power supply unit. Power consumption max. 2.5 Watt (2.1W at 24V) with full load, max. 1.1W (0.9W at 24V) without connections, IEEE 802.3az Energy Efficient Ethernet. Dimensions 70 x 115 x 41 mm, weight 300g.

- Physical Port
- 8-port 10/100BASE-TX RJ45 with auto MDI/MDI-X function
- Layer 2 Features
- Complies with IEEE 802.3 10BASE-T, IEEE 802.3u 100BASE-TX Ethernet standard
- Supports auto-negotiation and 10/100Mbps half/full duplex mode
- Prevents packet loss with back pressure (half-duplex) and IEEE 802.3x pause frame flow control (full-duplex)

- Complies with IEEE 802.3az Energy Efficient Ethernet (EEE)
- IEEE 802.1p CoS
- Supports 1K MAC address
- Automatic address learning and address aging
- Industrial Case / Installation
- IP30 metal case
- DIN rail and wall-mount design
- 12 to 48V DC, redundant power with polarity reverse protect function
- 24V AC power input acceptable
- Supports 6000 VDC Ethernet ESD protection
- -40 to 75 degrees C operating temperature
- Free fall, shock-proof and vibration-proof for industries
- Industrial usage: no
- Managed: no
- Outdoorsuitable: no
- PoE (Power over Ethernet): no
- Protection against vandalism: no
- VLAN: no

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm ³
Packaging Unit Carton	0	0.00	0.00	0.00	0.00	0.00
Packaging Unit Inside	0	0.00	0.00	0.00	0.00	0.00
Packaging Unit Single	1	0.30	0.00	0.00	0.00	0.00
Net single without Packaging	0	0.50	0.00	0.00	0.00	0.00

More images:

