

# Planet Industrial Switch, 8 x RJ45, 100 Mbps, -40/+75°C, Compact & Efficient

ISW-800T  
EAN 4711605282802



## Planet Industrial Switch, 8 x RJ45, 100 Mbps, -40/+75°C, Compact & Efficient

Très économe en énergie et compact! Commutateur Ethernet 8 ports, boîtier industriel IP30 pour montage sur rail DIN (rail DIN), également adapté au montage mural, 8 x RJ45 10/100Base-TX, Auto MDI/MDI-X, température de fonctionnement -40 à +75°C, protection ESD, entrées de courant redondantes 12-48V DC et 24V AC, livré sans bloc d'alimentation. Consommation d'énergie max. 2.5 Watt (2.1W à 24V) à pleine charge, max. 1.1W (0.9W à 24V) sans raccordements, Ethernet éconergétique IEEE 802.3az. Dimensions 70 x 115 x 41 mm, poids 300g.

- Physical Port
- 8-port 10/100BASE-TX RJ45 with auto MDI/MDI-X function
- Layer 2 Features
- Complies with IEEE 802.3 10BASE-T, IEEE 802.3u 100BASE-TX Ethernet standard
- Supports auto-negotiation and 10/100Mbps half/full duplex mode
- Prevents packet loss with back pressure (half-duplex) and IEEE 802.3x pause frame flow control (full-duplex)

- Complies with IEEE 802.3az Energy Efficient Ethernet (EEE)
- IEEE 802.1p CoS
- Supports 1K MAC address
- Automatic address learning and address aging
- Industrial Case / Installation
- IP30 metal case
- DIN rail and wall-mount design
- 12 to 48V DC, redundant power with polarity reverse protect function
- 24V AC power input acceptable
- Supports 6000 VDC Ethernet ESD protection
- -40 to 75 degrees C operating temperature
- Free fall, shock-proof and vibration-proof for industries
- Utilisation industrielle: Non
- Adapté pour un usage en extérieur: Non
- Managed: Non
- PoE (Power over Ethernet): Non
- Protection contre le vandalisme: Non
- VLAN: Non

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm <sup>3</sup>
Packaging Unit Carton	0	0.00	0.00	0.00	0.00	0.00
Packaging Unit Inside	0	0.00	0.00	0.00	0.00	0.00
Packaging Unit Single	1	0.30	0.00	0.00	0.00	0.00
Net single without Packaging	0	0.50	0.00	0.00	0.00	0.00

---

More images:

