

Planet Industrial Switch, 8 x RJ45, 100 Mbps, -40/+75°C, Compact & Efficient

ISW-800T
EAN 4711605282802



Planet Industrial Switch, 8 x RJ45, 100 Mbps, -40/+75°C, Compact & Efficient

Molto risparmio energetico e compatto! Interruttore Ethernet a 8 porte, alloggiamento industriale IP30 per montaggio su guida DIN (DIN Rail), adatto anche per montaggio a parete, 8 x RJ45 10/100Base-TX, Auto MDI/MDI-X, temperatura di esercizio -40 fino a +75°C, protezione ESD, ingressi di corrente ridondanti 12-48V DC e 24V AC, fornitura senza alimentatore. Potenza assorbita max. 2,5 Watt (2,1 W a 24 V) a pieno carico, max. 1.1W (0,9W a 24V) senza connessioni, IEEE 802.3az Energy Efficient Ethernet. Dimensioni 70 x 115 x 41 mm, peso 300g.

- Physical Port
- 8-port 10/100BASE-TX RJ45 with auto MDI/MDI-X function
- Layer 2 Features
- Complies with IEEE 802.3 10BASE-T, IEEE 802.3u 100BASE-TX Ethernet standard
- Supports auto-negotiation and 10/100Mbps half/full duplex mode
- Prevents packet loss with back pressure (half-duplex) and IEEE 802.3x pause frame flow control (full-duplex)
- Complies with IEEE 802.3az Energy Efficient Ethernet (EEE)
- IEEE 802.1p CoS
- Supports 1K MAC address
- Automatic address learning and address aging
- Industrial Case / Installation
- IP30 metal case
- DIN rail and wall-mount design
- 12 to 48V DC, redundant power with polarity reverse protect function
- 24V AC power input acceptable
- Supports 6000 VDC Ethernet ESD protection
- -40 to 75 degrees C operating temperature
- Free fall, shock-proof and vibration-proof for industries
- Uso industriale: no
- Adatto per esterni: no
- Gestito: no
- Power over Ethernet: no
- Protezione da atti vandalici: no
- VLAN: no

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm ³
Packaging Unit Carton	0	0.00	0.00	0.00	0.00	0.00
Packaging Unit Inside	0	0.00	0.00	0.00	0.00	0.00
Packaging Unit Single	1	0.30	0.00	0.00	0.00	0.00
Net single without Packaging	0	0.50	0.00	0.00	0.00	0.00

More images:

