

# MEAN WELL Power supply DIN rail 24 V, 5 A

**NDR-120-24**  
**EAN 7612946523326**



## Mean Well 120W 24V DC Industrial DIN Rail Power Supply (-20 to +70°C)

Single Output 120 Watt alimentation pour la planète commutateurs industriels et des convertisseurs. Entrée universelle 90-264V AC, sortie DC 24-28V (0-5A) Protection: Court-circuit / surcharge / surtension, pour montage sur rail DIN TS-35 / 7.5 / 15, Dimensions (LxHxP) 40x125.2x113.5mm

- Output voltage: 24 V
- Output current: max. 5 A

- Power: 120 W
- Ripple & noise: 150 mVpp
- Efficiency: 89% Universal AC input / full range
- Protections: short circuit, overload, over voltage, over temperature
- Cooling by free air convection
- Can be installed on DIN rail TS-35/7.5 or 15
- UL 508 approved
- EN61000-6-2 (EN50082-2) industrial immunity level
- 100% full load burn-in test

| Logistics                    |              |             |            |            |             |                 |
|------------------------------|--------------|-------------|------------|------------|-------------|-----------------|
|                              | Number (pcs) | Weight (kg) | Depth (cm) | Width (cm) | Height (cm) | cm <sup>3</sup> |
| Packaging Unit Carton        | 0            | 0.00        | 0.00       | 0.00       | 0.00        | 0.00            |
| Packaging Unit Inside        | 0            | 0.00        | 0.00       | 0.00       | 0.00        | 0.00            |
| Packaging Unit Single        | 1            | 0.60        | 0.00       | 0.00       | 0.00        | 0.00            |
| Net single without Packaging | 0            | 1.30        | 0.00       | 0.00       | 0.00        | 0.00            |

## More images:

