

# DIGITUS Zidni komunikacijski ormar Unique - 600x600 mm (ŠxD)

DN-19 09U-6/6  
EAN 4016032157519



**ORMAR 9U 60/60 DN19-9 509x600x600 mm, color grey (RAL 7035)**

Zidni komunikacijski ormari Unique proizvedeni su od čvrste čelične konstrukcije s minimalnim brojem spojeva. Bočni paneli mogu se skinuti i zaključati. Montaža ormara je brza i jednostavna. Dodatne nivelirajuće nožice ili kotačiće je moguće posebno naručiti. Zahvaljujući fleksibilnosti, ormari su idealni za sve trenutne IT i telekomunikacijske primjene.

**The DIGITUS® Unique Series is made for high demand IT-Infrastructure Solutions - designed and developed on highest standard in Germany**


- Safety class rating IP20
- Lockable safety-glass door with steel frame
- 210° door opening angle
- 1-point-locking-mechanism on the front door
- Side panels are lockable and removable
- 483 mm (19") profile rails mounted on the front- and rear side inside of the rack, galvanized
- 483 mm (19") profile rails are adjustable in depth and with height unit marking
- Max. installation depth: 450 mm

- Cable entry on the rear side and base with plastic cover and top with sliding cover
- Roof is prepared for fan units (punched out entries)
- Ventilation slots for active and passive ventilation and exhausting
- Several earthing points for rack components
- Incl. installation set (screws, cage nuts, washers)
- Rack is completely mounted
- Equipment mounting depth min.-max.: 320-450 mm
- Bočne ploče: Objе strane
- Boja: svijetlo siva, RAL 7035
- Dubina: 600 mm
- Jedinice: 9
- Kapacitet opterećenja: 100 kg
- Prednja vrata: Staklena vrata, jednostruko otvaranje
- Širina: 600 mm
- Vrsta ormara: Zidni ormarić
- IP klasa zaštite: IP20
- Montirano: Da

**Package contents**

- Earthing wire set
- Installation set (screws, cage nuts, washers)
- 2 x Keys

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	1	24.00	65.00	65.00	55.90	236,178.00
Packaging Unit Inside	1	24.00	65.00	65.00	55.90	236,178.00
Packaging Unit Single	1	24.00	65.00	65.00	55.90	236,178.00
Net single without Packaging	0	23.00	60.00	60.00	50.90	183.24

**More images:****Safety notes**

- Ensure adequate ventilation to prevent the installed devices from overheating.
- Network cabinets should not be overfilled and the ventilation openings must not be blocked.
- Cables should be laid neatly and organized in cable ducts or trays.
- Use surge protection devices to protect sensitive devices from power surges or lightning strikes.
- Avoid moisture or wetness while observing the respective IP protection class.
- Ensure that the cabinet and the devices used are properly earthed.
- In regions with frequent thunderstorm activity, professional lightning protection should be integrated into the power supply.
- To avoid uneven loading, always mount the heaviest units at the bottom of the cabinet.
- Disconnect the installed devices from the power supply during maintenance or installation work.

**EU responsible person**

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH  
Auf dem Schüffel 3  
Lüdenscheid, Germany  
<https://www.assmann.com>  
[info@assmann.com](mailto:info@assmann.com)