

# DIGITUS Ventilation Unit for variable 483 mm (19") installation

DN-19 FAN-4-HO-SW  
EAN 4016032189909



**VENTILATOR DN-19-FAN4/TERM.HO-SW**

The Roof Ventilation Units are variable mountable into 483 mm (19") cabinets. Each fan unit comes with two sets of mounting brackets. With the standard set you can install your fan unit into any height unit space of your network- or server cabinet. The second bracket set makes the fan unit possible to be mounted into the roof of 483 mm (19") network- or server cabinets of the varioFLEX series. A switch as well as an adjustable thermostat provides best options for customizations. The model is available in standard color grey (RAL 7035) and black (RAL 9005), equipped with either two or four fans.

- For installation into 483 mm (19") unit
- 4 fans
- incl. thermostat, adjustable from 0 °C up to +70 °C
- On/off switch
- Air flow: 9.2 m³/min.

- 1.8 m cable with CEE 7/7 (Type-F) plug
- 1.8 m cable with CEE 7/7 (Type F) plug

**Attributes**

- Boja: crna, RAL 9005
- Filtar: Ne
- Količina montiranih ventilatora: 4
- Područje za montažu: 482,6 mm (19")
- Protok zraka: 9.2 m³/min
- Za seriju ormara: svi

**Package contents**

- Mounting brackets for varioFLEX
- Mounting brackets for 19" profile rails
- Power cable
- Fixing material

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	5	29.90	30.00	50.00	42.50	63.75
Packaging Unit Inside	1	5.98	38.50	51.00	6.00	11.78
Packaging Unit Single	1	5.98	38.50	51.00	6.00	11.78
Net single without Packaging	0	4.28	48.00	30.00	4.60	6.62

**More images:**



**Safety notes**

- When installing and using the accessory product for network cabinets, observe the respective safety instructions of the manufacturer or the cabinet system in which you want to use the accessory.

**EU responsible person**

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH

Auf dem Schöffel 3

Lüdenscheid, Germany

<https://www.assmann.com>

[info@assmann.com](mailto:info@assmann.com)