

# DIGITUS Zidni ormari - SoHo, Slim

**DN-19 04U-PB**  
**EAN 4016032200109**



**ORMAR 5 U 19" D=140MM SLM007/NAPA SIVI 3U rotatable, 2U fix, color grey (RAL 7035)**

Zidni ormari SoHo, Slim savršeno su rješenje za smještaj aktivne i pasivne mrežne opreme. Karakterizira ih jednostavna i brza instalacija. Moderan dizajn odgovara svakom uredskom ili kućnom prostoru. Moguće su dvije odvojene instalacije: Prednja strana opremljena je sa 3U šinom koja se može rotirati. Alternativno, može se pozicionirati horizontalno ili čak pod kutom. Na stražnjoj strani nalazi se 2U šina (fiksno), koja se npr. može upotrijebiti za ugradnju pasivnih komponenti. Zbog izbušenih rupa za montažu na dnu kućišta može se instalirati ostala oprema koja nije predviđena za rack montažu (npr. DSL ruter, itd.).

**DIGITUS® wall-mounted enclosures are manufactured, designed and developed to meet the high demands of IT infrastructure.**

- Protection class IP20
- Lockable housing with transparent polycarbonate pane
- Upper part of the housing can be opened up to 80°
- Steel door stop mechanism keeps the door open
- 1-point four-point locking
- 2 separate 483 mm (19") installation options: 3U vertical (rotatable), 2U horizontal (fixed)
- Max. installation depth (from front vertical rail to stop on rear horizontal rail): Approx. 265 mm
- Max. installation depth (from front vertical rail to rear wall stop): Approx. 355 mm

- 2.0 mm thick sheet steel with a high load-bearing capacity, powder-coated
- Pre-punched cut-outs for cable routing
- Ventilation slots for active and passive ventilation
- Area for cable ties
- Lower housing area with punched-out mounting holes for mounting equipment that is not 483 mm (19") compatible
- Mounting plate is optionally available
- Fan mount dimensions: 57.5 x 57.5 mm
- Hole spacing for fan mounting: 50 x 50 mm (3.5 mm diameter)

**Attributes**

- Bočne ploče: Objе strane
- Boja: svijetlo siva, RAL 7035
- Dubina: 475 mm
- Jedinice: 5
- Kapacitet opterećenja: 30 kg
- Prednja vrata: Staklena vrata, jednostruko otvaranje
- Širina: 525 mm
- Vrsta ormara: Zidni ormarić, kućna automatika
- IP klasa zaštite: IP20
- Montirano: Da

**Package contents**

- 2 x key

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm <sup>3</sup>
Packaging Unit Carton	1	9.50	50.00	53.00	16.00	42.40
Packaging Unit Inside	1	9.50	50.00	53.00	16.00	42.40
Packaging Unit Single	1	9.50	50.00	53.00	16.00	42.40
Net single without Packaging	0	8.50	47.50	52.50	14.50	36,159.40

**More images:****Safety notes**

- Ensure adequate ventilation to prevent the installed devices from overheating.
- Network cabinets should not be overfilled and the ventilation openings must not be blocked.
- Cables should be laid neatly and organized in cable ducts or trays.
- Use surge protection devices to protect sensitive devices from power surges or lightning strikes.
- Avoid moisture or wetness while observing the respective IP protection class.
- Ensure that the cabinet and the devices used are properly earthed.
- In regions with frequent thunderstorm activity, professional lightning protection should be integrated into the power supply.
- To avoid uneven loading, always mount the heaviest units at the bottom of the cabinet.
- Disconnect the installed devices from the power supply during maintenance or installation work.

**EU responsible person**

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH  
Auf dem Schüffel 3  
Lüdenscheid, Germany  
<https://www.assmann.com>  
[info@assmann.com](mailto:info@assmann.com)