

DIGITUS Wall Mounting Patch Bracket for 483 mm (19") Installations

DN-19 PB-2U
 EAN 4016032205982



2U wall mounting patch bracket, 106x505x250 mm adjustable depth, stackable, grey (RAL 7035)

The Wall Mounting Patch Brackets for 483 mm (19") installations are used for open mountings of 483 mm (19") components. They are available in several height units to suit to your individual needs of space. The brackets are adjustable in depth (from 225 mm up to 399 mm) which makes the installation of larger components possible. The rear side has a big cut-out area that can be used to guide cables which come directly from the wall.

- for installation of 483 mm (19") components
- 1.1 - 1.5 strong sheet steel, powder coated
- adjustable depth (min. 225 mm; max. 399 mm)
- with four holes for wall mounting

- rear side with cut-out e.g. for cabling
- Bočne ploče: bez
- Boja: svijetlo siva, RAL 7035
- Jedinice: 2
- Kapacitet opterećenja: 15 kg
- Prednja vrata: bez
- Širina: 505 mm
- Vrsta ormara: Zidni ormarić
- IP klasa zaštite: bez
- Montirano: Ne

Package contents

- Fixing material for stacking

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm ³
Packaging Unit Carton	1	2.32	11.50	53.00	4.00	2.44
Packaging Unit Inside	1	2.32	11.50	53.00	4.00	2.44
Packaging Unit Single	1	2.32	11.50	53.00	4.00	2.44
Net single without Packaging	0	0.00	25.00	50.50	10.60	13,382.50

More images:



