

# DIGITUS Zidni komunikacijski ormar Dynamic Basic - 600x600 mm (ŠxD)

DN-19 09U-6/6-EC  
EAN 4016032221746



## ORMAR 9U 60/60 DN19-09U-6/6-EC 505x600x600 mm, color grey (RAL 7035)

Zidni komunikacijski ormari Dynamic Basic proizvedeni su od čvrste čelične konstrukcije. Zavareni spojevi osiguravaju stabilnost. Bočni paneli mogu se skinuti, a ormar na zid možete jednostavno i brzo montirati. Zahvaljujući fleksibilnosti, ormari su idealni za sve trenutne IT i telekomunikacijske primjene.

- Safety class rating IP20
- Lockable safety-glass door with steel frame
- 235° door opening angle
- 1-point-locking-mechanism on the front door
- 483 mm (19") profile rails mounted on the front- and rear side inside of the rack, galvanized
- 483 mm (19") profile rails are adjustable in depth and with height unit marking
- 0.8 - 1.2 mm strong sheet steel with high load capacity, powder coated
- Cable entry on the rear side, roof and base (pre-punched break-outs)

- Roof is prepared for fan units (punched out entries)
- Ventilation slots for active and passive ventilation and exhausting
- 4 earthing points (base, side panel and front door) with protection cap
- Equipment mounting depth min.-max.: 320 - 450 mm
- Bočne ploče: Obje strane
- Boja: svijetlo siva, RAL 7035
- Dubina: 600 mm
- Jedinice: 9
- Kapacitet opterećenja: 60 kg
- Prednja vrata: Staklena vrata, jednostruko otvaranje
- Širina: 600 mm
- Vrsta ormara: Zidni ormarić
- IP klasa zaštite: IP20
- Montirano: Da

### Package contents

- Earthing wire set
- Installation set (screws, cage nuts, washers)
- 2 x Keys

## Logistics

	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm <sup>3</sup>
Packaging Unit Carton	1	25.00	64.00	64.00	51.00	208.90
Packaging Unit Inside	1	25.00	64.00	64.00	51.00	208.90
Packaging Unit Single	1	25.00	64.00	64.00	51.00	208.90
Net single without Packaging	0	24.00	60.00	60.00	47.40	170.64

More images:

