

DIGITUS CAT 6, modular couplers, shielded

AT-AG 8/8 C6S
EAN 4016032229032



AT-AG 8/8 c6s spojnic 2xRJ45 c6 FTP shielded CAT6, metal housing

The modular CAT 6 coupler from DIGITUS® consists of two shielded RJ45 sockets. The assignment is "1:1".

- Technical properties:
- Housing material: ABS UL-94V-0
- Contacts coating: Nickel, gold-plated 0.5 μ

- Shielding: Tinned bronze
- PCB:FR4, UL 94V-0
- Material contacts: Phosphor bronze
- Physical properties:
- Mating cycles: ≥ 750 (ISO/IEC 11801, IEC 60603-7-5)
- Insertion force: 30N max. (IEC 60603-7-5)
- Retention strength: 7.7 kg between jack and plug

| Logistics | | | | | | |
|------------------------------|--------------|-------------|------------|------------|-------------|-----------------|
| | Number (pcs) | Weight (kg) | Depth (cm) | Width (cm) | Height (cm) | cm ³ |
| Packaging Unit Carton | 500 | 9.80 | 54.00 | 35.00 | 12.00 | 22.68 |
| Packaging Unit Inside | 50 | 0.98 | 22.00 | 20.00 | 6.00 | 2.64 |
| Packaging Unit Single | 1 | 0.02 | 4.00 | 2.00 | 2.00 | 16.00 |
| Net single without Packaging | 0 | 0.03 | 0.00 | 0.00 | 0.00 | 0.00 |