

# DIGITUS CAT 6, modular couplers, shielded

**AT-AG 8/8 C6S**  
**EAN 4016032229032**



**AT-AG 8/8 c6s spojnică 2xRJ45 c6 FTP shielded CAT6, metal housing**

The modular CAT 6 coupler from DIGITUS® consists of two shielded RJ45 sockets. The assignment is "1:1".

- Technical properties:
- Housing material: ABS UL-94V-0
- Contacts coating: Nickel, gold-plated 0.5 μ

- Shielding: Tinned bronze
- PCB:FR4, UL 94V-0
- Material contacts: Phosphor bronze
- Physical properties:
- Mating cycles: ≥ 750 (ISO/IEC 11801, IEC 60603-7-5)
- Insertion force: 30N max. (IEC 60603-7-5)
- Retention strength: 7.7 kg between jack and plug

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm <sup>3</sup>
Packaging Unit Carton	500	9.80	54.00	35.00	12.00	22.68
Packaging Unit Inside	50	0.98	22.00	20.00	6.00	2.64
Packaging Unit Single	1	0.02	4.00	2.00	2.00	16.00
Net single without Packaging	0	0.03	0.00	0.00	0.00	0.00

**Safety notes**

- Protect product from moisture
- Avoid antistatic charging when installing the product
- Observe the specifications of the raw cable manufacturer during installation

**EU responsible person**

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH  
 Auf dem Schüffel 3  
 Lüdenscheid, Germany  
<https://www.assmann.com>  
[info@assmann.com](mailto:info@assmann.com)