


DIGITUS Kat. prespojni panel klase D

DN-91524S
EAN 4016032241522



DN-91524S P.PAN.19" C5E STP-D RJ45, 8P8C, LSA, 1U, rack mount, grey, 482x44x109

Oklopljeni prespojni panel Kat. 6 iz DIGITUS® ponude dostupan je kao 16 ili 24 portni panel. Sukladan je ISO/IEC 11801 i EN 50173. Kućište je proizvedeno od pocinčanog hladno valjanog čelika debljine 1,5 mm i zato je savršen za 19" rack montažu.

Future-oriented standards and high-end quality for your network.

- Transmission properties: Category 5e
- Area of application: Up to 100 MHz, 10/100Base-T, 1GBase-T
- Norms: ISO/IEC 11801 3rd Ed., EN 50173-1, EIA/TIA 568-C
- General properties:
- Suitable for 483 mm (19") cabinet mounting
- RJ45 female, 8P8C
- Cable installation via LSA strips, color coded according to EIA/TIA 568 A & B
- Cable fixing with smart cable ties
- Central ground connection
- 360° shield coverage
- Mechanical properties:
- Housing material: 1.5 mm galvanic cold rolled steel, acc. to EN1.4301, UNS S30400, AISI 304 and LMSAD110
- RJ45 female material: ABS UL 94V-0

- RJ45 female contact: Tinned phosphor bronze, 0.5 µ gold-plated contact
- RJ45 shielding: Tinned bronze
- LSA termination clamp: Krone LSA+, UL 94V-2, zinc plated phosphor bronze
- Ground wire: Not included
- Conductor plate: FR4, UL 94V-0
- Physical properties:
- Insertion force: 30N max. (IEC 60603-7-5)
- Retention strength: 7.7 kg between jack and plug
- Operation temperature: -20° C to +70 °C (ISO/IEC 11801, EN 50173-1, ANSI/TIA/EIA 568 C)
- Mating cycles female: > 750 acc. to ISO/IEC 11801, IEC 60603-7-5
- Clamp: > 200 acc. to ISO/IEC 11801, IEC 60603-7-5
- IDC wire size: 22 – 26 AWG solid and stranded conductor
- Insulation resistance: > 500 MOhm
- Contact resistance: < 20 MilliOhm
- Dielectric strength: 1000 VDC (Contact/Contact), 1500 VDC (Contact/Ground)
- Boja: svijetlo siva, RAL 7035
- Jedinice: 1
- Priključci: 24
- Kategorija: CAT 5e

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	10	16.60	53.00	29.00	30.50	46,878.50
Packaging Unit Inside	1	1.66	8.00	56.00	15.00	6.72
Packaging Unit Single	1	1.66	8.00	56.00	15.00	6.72
Net single without Packaging	0	1.50	4.50	48.50	11.00	2,400.75

More images:

