

DIGITUS Zidni komunikacijski ormar Dynamic Basic - 600x450 mm (ŠxD)

DN-19 16-U-EC-SW
EAN 4016032257844



16U wall mounting cabinet 816.20x600x450 mm, color black (RAL 9005)

Zidni komunikacijski ormari Dynamic Basic proizvedeni su od čvrste čelične konstrukcije. Vareni spojevi osiguravaju stabilnost. Bočni dijelovi mogu se skinuti, a ormar na zid možete jednostavno i brzo montirati. Zahvaljujući fleksibilnosti, ormari su idealni za sve trenutne IT i telekomunikacijske primjene.

- Safety class rating IP20
- Lockable safety-glass door with steel frame
- Lockable safety glass door with steel frame
- 1-point-locking-mechanism on the front door
- 483 mm (19") profile rails mounted on the front- and rear side inside of the rack, galvanized
- 483 mm (19") profile rails are adjustable in depth and with height unit marking
- 0.8 - 1.2 mm strong sheet steel with high load capacity, powder coated
- Cable entry on the rear side, roof and base (pre-punched break-outs)

- Roof is prepared for fan units (punched out entries)
- Ventilation slots for active and passive ventilation and exhausting
- 4 earthing points (base, side panel and front door) with protection cap
- Equipment mounting depth min.-max.: 335 -380 mm
- Bočne ploče: Obje strane
- Boja: crna, RAL 9005
- Dubina: 450 mm
- Jedinice: 16
- Kapacitet opterećenja: 60 kg
- Prednja vrata: Staklena vrata, jednostruko otvaranje
- Širina: 600 mm
- Vrsta ormara: Zidni ormarić
- IP klasa zaštite: IP20
- Montirano: Da

Package contents

- Earthing wire set
- Installation set (screws, cage nuts, washers)
- 2 x Keys

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm ³
Packaging Unit Carton	1	34.00	48.00	64.00	82.00	251.90
Packaging Unit Inside	1	34.00	48.00	64.00	82.00	251.90
Packaging Unit Single	1	34.00	48.00	64.00	82.00	251.90
Net single without Packaging	0	32.00	45.00	60.00	78.50	211.95

More images:

