

DIGITUS ISDN prespojni panel Kat. 3, neoklopljeni, sivi

DN-91325-1
EAN 4016032269007



DN-91325 P.PAN.19" C3 25 PORT SIVI-D RJ45, 8P4C, LSA, 1U, rack mount, grey, 482x44x109

ISDN prespojni panel iz DIGITUS® ponude dostupan je kao 25 ili 50 portni panel. Kućište je proizvedeno od pocinčanog hladno valjanog čelika debljine 1,5 mm i zato je savršen za 19" rack montažu.

Future-oriented standards and high-end quality for your network.

- Suitable for 483 mm (19") rack mount
- Suitable for cables with AWG 22-26 diameter
- Material housing: SECC, 1.5 mm electrogalvanized, cold-rolled steel acc. EN1.4301, UNS S30400, AISI 304 and LMSAD110
- RJ45 female, 8P4C
- Unshielded RJ45 jacks
- Material contacts: Phosphor bronze
- Contacts coating: Nickel, gold plated 0,3µ

- Cable installation via LSA strips, color coded according to EIA/TIA 568 A & B
- Material IDC Terminal: Phosphor bronze with 50 µ tin plated over 60 µ nickel plated
- Material PCB: FR4, UL 94V-0, multilayer 1.45 mm thickness
- Insertion force: ≤ 30 N
- Mating cycles: ≥ 750 (ISO/IEC 11801, IEC 60603-7-5)
- Operating temperature: -20°C ... +70°C
- Current carrying capacity: 1A at 50 °C
- Isolation resistance > 500MΩ
- Color: Grey (RAL 7035)
- Boja: svijetlo siva, RAL 7035
- Jedinice: 1
- Priključci: 25
- Kategorija: CAT 3

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	10	14.46	53.50	32.00	28.00	47.94
Packaging Unit Inside	1	1.45	5.20	51.30	14.80	3,948.05
Packaging Unit Single	1	1.45	51.50	5.50	10.50	2,974.12
Net single without Packaging	0	0.96	10.00	48.20	4.30	2,072.60

More images:

