

# DIGITUS pigtail-ovi u boji, LC OM2 50/125 μ, simpleks

DK-25332-02  
EAN 4016032280163



## AL 5FPLC-02-SET PIGTAIL 50μm, 12 kom-D loose buffer, color code DIN IEC 304, 2m

DIGITUS® optički pigtail-ovi u boji dostupni su kao LC simpleks, SC simpleks i ST simpleks verziji i u ponudi u klasama OS2, OM2, OM3 i OM4 nude najbolje performanse i kvalitetu linka Vaše mreže. Konektor je sukladan IEC 61754-4 2002 i opremljen je s keramičkom ferulom od cirkonija. Pigtail-ovi u boji kodirani su sukladno IEC 304 (bijeli, ljubičasti, tirkizni, crni, crveni, rozi, narančast, sivi, zeleni, žuti, smeđi, plavi).

### Vrhunsku kvalitetu Vaše mreže osigurava oprema izrađena sukladno najnovijim standardima.

- Standard konektora sukl. IEC 61754-4 2002
- Radna temperatura: -25 °C ... +80 °C
- Temperatura skladištenja: -20 °C ... +65 °C
- Insertion loss MM PC: maks. 0.4 dB
- Return loss MM PC: > 25 dB

- Keramička ferula od cirkonija
- Simpleks OM2 50/125 μ 2 m
- Dimenzije sekundarnog plašta: Ø 0,9 ± 0,1 mm
- Primarni premaz: Akrilat; Ø 250 ± 15 μm
- Obojeni sukladno IEC 304: bijela, ljubičasta, tirkizna, crna, crvena, roza, narančasta, siva, zelena, žuta, smeđa, plava
- 12 kom. u pakiranju
- Loose buffer

### Attributes

- Kabelski omotač: LSOH
- Klasa vlakna: OM2
- Konektor 1: LC
- Mod: Višemodni
- Promjer vlakna: 50/125μ
- Stopica: jednobojna
- Duljina: 2 m

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm <sup>3</sup>
Packaging Unit Carton	160	7.20	41.00	41.00	28.00	47.07
Packaging Unit Inside	20	0.90	19.00	19.00	12.00	4.33
Packaging Unit Single	1	0.05	17.00	17.00	1.00	289.00
Net single without Packaging	0	0.05	15.00	15.00	1.00	225.00

### Safety notes

- Avoid direct contact with light sources: Fiber optic cables, especially those with active light sources such as lasers (e.g. in optical communication systems), can emit dangerous radiation that can damage eyes. Take care never to look directly into the light of an optical fiber, even if the light source is invisible to the naked eye.
- When working with fiber optic cables, especially during tests or when working with lasers, protective goggles should always be worn to protect against harmful radiation.
- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Do not kink or crush: Fiber optic cables are sensitive to mechanical stress.
- To protect cables from physical damage, they should be laid in special ducts or with protective materials
- Keep cable connectors clean: Fiber optic cables are sensitive to dust and dirt. Even small particles on the connectors can severely impair the signal quality.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product information on the maximum operating temperature of the cable

- Check cables regularly for visible damage such as cracks, kinks or signs of wear. Defective cables should be replaced immediately.

**EU responsible person**

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH  
Auf dem Schüffel 3  
Lüdenscheid, Germany  
<https://www.assmann.com>  
[info@assmann.com](mailto:info@assmann.com)