


DIGITUS modularni prespojni panel, 16 portni

DN-91400
EAN 4016032280750



PANEL KEYSTONE 16-PORTNI 1U 19" Ral:9005 blank, 1U, rack mount, black RAL 9005

Modularni prespojni panel iz DIGITUS® ponude dostupan je kao 16 ili 24 portni panel. Okvir je proizveden od pocinčanog hladno valjanog čelika debljine 1,5 mm i osigurava siguran prihvata Vaših keystone utičnih modula.

- Layout Keystone Entry: Double-row
- Area of application: 483 mm (19") cabinet
- Norms: ISO/IEC 11801 3rd Ed., EN 50173-1, EIA/TIA 568-C
- General properties:
- Suitable for 483 mm (19") cabinet mounting
- Suitable for unshielded Digitus® Keystone Modules and Couplers

- Technical properties:
- Housing material: 1.5 mm SPCC cold rolled steel sheet, powder-coated
- Material standard: EN 10 130(1991), BS 1449, NFA 36/401, DIN 1623, UNI 5866, UNE 36-086, SIS, JIS G 3141, ASTM, SAE, NFA 36/401
- Physical properties:
- Operation temperature: -20° C to +70 °C (ISO/IEC 11801, EN 50173-1, ANSI/TIA/EIA 568 C)
- Colour: Black RAL9005
- Boja: crna, RAL 9005
- Jedinice: 1
- Priključci: 16

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	64	22.02	58.00	24.00	25.00	34.80
Packaging Unit Inside	8	2.75	56.50	10.00	7.50	4,237.50
Packaging Unit Single	1	0.34	48.50	4.30	1.50	312.83
Net single without Packaging	0	0.00	0.00	0.00	0.00	0.00