

DIGITUS Modular Patch Panel, 24-port staggered

DN-91412
EAN 4016032295105



PANEL KEYSTONE 24-PORTNI 1U 19" DN-91412 Ral:7035- blank, 1U, rack mount, staggered, bl RAL 9005

The staggered modular 24-port Patch Panels from DIGITUS® are with the 1.5 mm cold rolled c-steel perfect suitable for 483 mm (19") rack mounting. Due to the staggered array of the keystone modules a better attenuation ratio is reached between surrounding transmission channels. They are available in the colors grey (RAL 7035) and black (RAL 9005).

- Layout Keystone Entry: Staggered
- Area of application: 483 mm (19") cabinet
- Norms: ISO/IEC 11801 3rd Ed., EN 50173-1, EIA/TIA 568-C
- General properties:
- Suitable for 483 mm (19") cabinet mounting
- Suitable for shielded Digitus® Keystone Modules and Couplers

- Central ground connection
- Technical properties:
- Housing material: 1.5 mm SPCC cold rolled stell sheet, powder-coated
- Material standard: EN 10 130(1991), BS 1449, NFA 36/401, DIN 1623, UNI 5866, UNE 36-086, SIS, JIS G 3141, ASTM, SAE, NFA 36/401
- Grounding bar material: Galvanized steel
- Physical properties:
- Operation temperature: -20° C to +70 °C (ISO/IEC 11801, EN 50173-1, ANSI/TIA/EIA 568 C)
- Colour: Black RAL9005
- Boja: crna, RAL 9005
- Jedinice: 1
- Priključci: 24

| Logistics | | | | | | |
|------------------------------|--------------|-------------|------------|------------|-------------|-------|
| | Number (pcs) | Weight (kg) | Depth (cm) | Width (cm) | Height (cm) | cm³ |
| Packaging Unit Carton | 15 | 13.19 | 56.00 | 40.00 | 30.00 | 67.20 |
| Packaging Unit Inside | 1 | 0.88 | 5.00 | 54.00 | 15.00 | 4.05 |
| Packaging Unit Single | 1 | 0.88 | 5.00 | 54.00 | 15.00 | 4.05 |
| Net single without Packaging | 0 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |

More images:

